
The LBS (Low Bees Stress) Method Package Installation on Drawn Comb Tony Rimkus www.olddrone.net



Be Prepared:

- Package Box
- Bee Brush
- Hive Tools
- Magnet
- Spray Bottle with Sugar Water
- Rubber Bands
- 2 blocks of wood
- Thin Nail

- 1. Remove 2 frames of drawn comb of honey
- 2. Cut out a rectangle on each of the frames, large enough for queen cage to rest in.
- 3. Spray bees lightly with sugar-water
- 4. Rap box on ground to dislodge bees from top of container
- 5. Remove plywood from top of package box
- 6. Use Magnet to remove metal container
- 7. Remove Queen cage
- 8. Put plywood back on top of package box to keep bees inside





- 1. Remove cork from candy end of queen cage
- 2. Use nail to pierce a hole part-way through candy
- 3. Place queen cage into cut-out on frame.
- 4. Push frames together





Top down view



1. Put frame with queen cage attached back into the middle of the frames. Insert remaining frame on outside.

- 1. Put wood blocks to the side, near the queen cage
- 2. Remove lid from package
- 3. Place upside down on top of blocks
- 4. Close up hive.
- 5. Remove package box within 24 hours
- 6. Check queen cage in 3 days. If empty, remove. If queen is still in cage, enlarge hole and check back in 2 days. Remove cage

