

201-504-502-UV2

HDMI 2.0 Switch 5x1, 4K x 2K/60Hz 3D with IR control, CEC

This 5x1 HDMI switch allows five HDMI ports to be switched to a single display terminal via remote control or buttons on unit. This switch can also be placed at the end of a long HDMI cable to regenerate the HDMI signal. For easier switch, it comes with IR remote control for quickly change inputs.

It supports video formats including 720p, 1080i, 1080p, 4K@30Hz, 4K@60Hz. And, it includes an automatic switching based on the active device. It can have an instant switch the input to the cable. It has a unique iron box design that helps to keep it cool during extended gaming marathons.



FEATURES

- Support 6Gbps data rate for tmds clock up to 600MHz
- Support HDMI 2.0a
- Support 3D
- Supports highest video resolution 4K/60Hz
- Support 24/ 30/ 36 bit deep color
- Support AWG26 HDMI standard cable, input/output by 8m (4K@30Hz resolution) and input/output distance by 3-5m (4K@60Hz resolution)
- Support single high definition display for multiple sources, such as DVD Players and HD player, PS4, Set Top Boxes
- Remote control for operational flexibility and easy to control

SPECIFICATIONS

HDMI Signal	HDMI 2.0a
HDMI Resolution	Up to 4K@ 60Hz
Support Video Color Format	24/ 30/ 36 bit deep color, 3D
Support Audio Format	DTS-HD/ Dolby-true HD/ DTS/ Dolby-AC3/ DSD
Max Bandwidth	600MHz
Max Baud Rate	6Gbps
Input Cable Distance	<8m AWG26 HDMI cable for 4K@ 30Hz, 3m for 4K@ 60Hz
Output Cable Distance	<8m AWG26 HDMI cable for 4K@ 30Hz, 5m for 4K@ 60Hz
Max. Working Current	600mA
Power Adapter Format	Input AC (50Hz, 60Hz) 100V-240V; Output DC5V/1A
Operation Temperature	-15°C to +55°C
Power Supply	DC5V/1A
Dimensions (L x W x H)	178 x 58 x 20mm
Weight	225g
Accessories Included	IR Remote Control x 1; 5V1A DC Power Supply x 1; User Manual x 1

ORDERING INFORMATION

201-504-502-UV2

HDMI 2.0 Switch, 5x1, 4K x 2K 3D, with remote