

LO-K-TOR SERIES SKID MOUNTED VACUUM EXCAVATOR

Our skid mounted, portable vacuum excavator is designed to chain or bolt to your vehicle, trailer or other equipment.

Free up equipment for other uses; only mount the Lo-K-Tor when needed.

FEATURES:

- Fits in the back of a pick-up truck
- Effortless Dumping - pump reverses and spoil is blown out
- Works at greater depth
- Works horizontally further from the machine for sewer and water pipe jobs
- No vacuum filters to buy
- Low profile trailer and heavy duty construction for outstanding durability
- Very competitive pricing
- Efficient design requires less maintenance
- Durable - all hoses, fittings and couplings are made of high quality materials
- Designed to be economical to purchase, operate and maintain

There are endless applications for the Lo-K-Tor including:

- Locating underground utilities without impact damage
- Cleaning catch basins and storm drains of debris
- Cleaning irrigation canals/ditches
- Assisting in storm damage clean-up
- Digging shallow wells
- Digging trenches / Slot Trenching
- Assisting in emergency road spill clean up
- Removing wet OR dry material
- Keyholing or utility microsurgery
- Cleaning up hazardous material
- Digging post holes



**IF YOU NEED IT,
WE WILL BUILD IT!**

LKT75S**LKT150S****SKID**

| | | |
|------------|---------------|---------------|
| Dimensions | 48" W X 78" L | 48" W X 78" L |
|------------|---------------|---------------|

VACUUM

| | | |
|------------|--|--|
| Pump | Jurop PN23D - Reverses to facilitate high-speed dumping | Jurop PN23D - Reverses to facilitate high-speed dumping |
| Pump Motor | Self-contained & powered by a 13.5 HP Honda engine with electric start and battery | Self-contained & powered by a 20 HP Honda or Kohler engine with electric start and battery |
| Pressure | Max Vac 90% / 27 inHg Continuous Vac 60% / 18 inHg | Max Vac 90% / 27 inHg Continuous Vac 60% / 18 inHg |
| Accessory | 50 feet of 2 inch vacuum hose with cam-lock connectors | 50 feet of 3 inch vacuum hose with cam-lock connectors |

SPOILS TANK

| | | |
|-----------|---|---|
| Capacity | 75 gallons | 150 gallons |
| Safety | Equipped with over-flow shut off valves inside the tank primary & secondary | Equipped with over-flow shut off valves inside the tank primary & secondary |
| Clean Out | Mounted at an angle for easier clean out, 12" access hatch and 3" valve in rear of tank | Mounted at an angle for easier clean out, 12" access hatch and 3" valve in rear of tank |

EXCAVATION

| | | |
|------------------|--|--|
| Pressure Pump | AR piston pressure pump produces 3000 psi of working pressure at 2.8 gpm | AR piston pressure pump produces 3000 psi of working pressure at 2.8 gpm |
| Fresh Water Tank | 50 gallon polyethylene tank | 50 gallon polyethylene tank |
| Pump Motor | Honda GC190 | Honda GC190 |
| Accessory | 50 feet of 4000 psi pressure hose & 5' wand with turbo tip attachment | 50 feet of 4000 psi pressure hose & 5' wand with turbo tip attachment |



**CUSTOM PAINT TO MATCH YOUR COMPANY COLORS OR STANDARD BLACK,
YOUR COMPANY LOGO, OTHER MODELS AND CUSTOM BUILDS AVAILABLE**