

# Selectable Gallonage Nozzle

## Style 366

- Combination pattern nozzle with versatile multiple flow settings
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Lightweight hardcoat anodized aluminium construction
- Available in tip only and shutoff combinations
- Standard operating pressure at 100 psi (7bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Standard NH inlet or optional BIM / Machino / Storz inlets
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)



Raised lug for flashover fog pattern



Newly improved handle with two reinforced pieces on each side to prevent breakage



## Specification


Style	Inlet Size	Length	Weight Lbs(kg)	Flow Settings	
				GPM	LPM
366	1-1/2" (38mm)	9" (228mm)	3.9 (1.7kg)	30-60-95-125	115-230-360-475



# Selectable Gallonage Nozzle

Style 366

## Unique Features On Protek Nozzles



### Technical Data



Style	Nozzle Pressure		Flow Setting		Actual Flow		Straight Stream Reach			
	PSI	BAR	GPM	LPM	GPM	LPM	Effective		Overall	
							Feet	Meters	Feet	Meters
366	75	5	30	115	26	98	80	24	90	27
			60	230	52	197	100	30	110	34
			95	360	82	310	120	36	130	39
			125	475	108	409	130	40	140	42
	100	7	30	115	30	115	85	26	95	29
			60	230	60	230	105	30	115	35
			95	360	95	360	125	38	135	41
			125	475	125	475	140	42	150	45
	125	8.5	30	115	34	129	90	27	100	30
			60	230	67	254	110	34	120	36
			95	360	107	401	125	38	135	41
			125	475	140	530	135	41	145	44

