



C3200		
TECHNICAL SPECIFICATIONS	Power Source	110V/15A
	Cord Length	10' / 3.0M
	Drive Motor	
	Incline Motor	1,000 lbs. of thrust
	Speed Sensor	Optical
		1" / 0.8 cm Medium Density Fiberboard
		Siegling Multi-Ply with PVC Coating
		3" / 8 cm w/ Sealed Bearings
		True Soft System
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Lubrication	
	Speed Range	0.5 to 12.0 MPH / 0.8 to 19.3 KMH
	Incline/Decline Range	0% to 15%
	Quick Access Control	Speed, Incline, Start and Stop on Quick Access Point
	Handrail Design	Extended Handrails with Molded Rubber, Moisture Resistant Grips
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
CONSOLE	Display	LCD
	Programs	12
	HRC Workouts	1
	HRC Cruise Control	Standard
	CSAFE Power	Standard
	Diagnostic	Standard
SAFETY	Saftey Clip	Standard
	Extended Handrails	Standard
	Large Straddle Covers	Standard
REGULATORY APPROVALS		ETL, UL1647, CSA, (CE for 220 v)
PHYSICAL SPECIFICATIONS	Footprint	82.5" L x 35.5" W / 210 cm x 90 cm
	Running Surface	60" L x 22" W / 152 cm x 56 cm
	Machine Weight	349 lbs / 159 kg
	Shipping Weight	424 lbs / 193 kg
	Maximum User Weight	350 lbs / 159 kg
	Step-Up Height	6.25" / 16 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)
	Frame	Lifetime
	Motor	5 Years
	Parts	5 Years
	Labor	1 Year

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.















