



MSDS

- | | |
|---------------------------|---|
| 1. Product: | Silvermax Roofing Underlayment |
| 2. Usage/Description: | Both side coated polypropylene woven fabric used as an air, Water and vapor barrier for roofing underlayment. |
| 3. Composition: | 90% polypropylene & 10% olefin copolymer, UV, Anti-oxidant & dye master batch. |
| 4. Physical States: | Solid fabric form in rolls. |
| 5. Odor: | Odorless |
| 6. Flammability: | Contribute but not flammable |
| 7. Hazardous ingredients: | Non-hazardous product |
| 8. Hazardous Combustion: | Carbon Monoxide, Carbon Dioxide, Nitrogen Oxides |
| 9. Means of extinction: | Dry chemical or water spray. |
| 10. Handling and Storage: | Good air ventilation without extreme temperature variance. |
| 11. Waste Disposal: | Recycle materials & bio-degradable.
See your local authorities for disposal instructions. |

Disclaimer:

This information is furnished without warranty expressed or implied, except that it is accurate to the best knowledge of GT International Distributions Company Ltd.