

### **PRODUCT DATASHEET**

## HFC-WSR-03

# CONVENTIONAL WALL SOUNDER

The HFC-WSR-03 Conventional Wall Sounder forms the core of our modular alarm device range. The unit can either be used as a standalone conventional device or as an intelligent unit by the addition of a wired module (HFI-SIM-01) or wireless module (HFW-SIM-01). All devices are weather proof, therefore this combined with the modular approach means the majority of applications can be achieved with very few stock components. The unit is equipped with 3 levels of volume adjustment and 32 recognised tones which can be set via the control equipment or locally at the sounder.

#### **KEY FEATURES**

- Flexible modular design, compatible with Hyfire intelligent & wireless modules
- 5 year product warranty
- 3rd party approval to EN54-3
- 32 Tone Settings
- Two stage alarm capability
- Weatherproof as standard
- Easy to install
- High sound output capability
- On site adjustable volume settings
- Microphone self test facility
- Robust with high reliability

Note: Functionality is dependant on the control equipment and module selection.

## **TECHNICAL SPECIFICATION**

- Power supply voltage range 15Vdc – 40Vdc
- Activated current load (High Vol.) 5-8 mA at 24 Vdc
- Acoustic Frequency range 400-2900 Hz
- Maximum acoustic Output
- Operating temperature range
- Unit weight (inc Back box)
- Max humidity (non condensing) 95% RH
- **IP** Rating

HFC-WSR-03\_H\_DSH\_066-

- 100 dB(A) @ 1m
- - -25°C to +70°C (no icing) 290q

65








928w


Note: Certified device performance may vary depending on the approval body.

Sterling Safety Systems Ltd Unit B12a, Holly Farm Business Park, Honiley, Warwickshire CV8 1NP

T: 01926 485282 E: info@sterlingsafety.co.uk www.sterlingsafety.co.uk



**TECHNICAL INFORMATION** 



# **STANDARDS & APPROVALS**

0832