

# Selectable Gallonage Nozzles

## Style 360, 361, 362



- Combination pattern nozzles with versatile multiple flow settings
- Produces straight stream for maximum reach and superb wide fog pattern for optimum fire fighter protection
- Available in either lightweight hardcoat anodized aluminium or corrosion resistant brass construction
- Available in tip only and shutoff combinations
- Standard operating pressure at 100 psi (7bar), optional 85 psi (6 bar) or 75 psi (5 bar)
- Can be used for high pressure applications of up to 580 psi (40 bar) hydrostatic pressure
- Minimal maintenance reflected in robust design, precision machining and quality materials
- Standard NH inlet or optional BIM / Machino / Storz inlets
- Compatible with Protek's foam aeration tubes
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoffs and Tips)

## Specification

Style	Inlet Size	Length	Weight LBS	Flow Settings	
				GPM	LPM
360	1" (25mm)	7.4" (190mm)	2.3 (1.1kg)	5-10-24-40	19-37-90-150
361	1" (25mm)	7.4" (190mm)	2.3 (1.1kg)	13-25-40-60	50-100-150-230
362	1" (25mm)	7.4" (190mm)	2.3 (1.1kg)	12-23-30	50-90-115

# Selectable Gallonage Nozzles

## Unique Features On Protek Nozzles

