

5.000" OD DRILL PIPE, 19.50 PPF, 6.500" OD X 3.500" ID, VM-105 DP SS, NC50 EIS™-L

DRILL PIPE BODY

Nominal Weight (lbs/ft)	19.50	
Grade	VM-105 DP SS	
Type of Upset	IEU	
	New	Premium
Nominal OD (in)	5.000	4.855
Nominal ID (in)	4.276	4.276
Pipe Wall Thickness (in)	0.362	0.290
Cross Sectional Area of Pipe Body (in ²)	5.275	4.152
Cross Sectional Area OD (in ²)	19.635	18.513
Cross Sectional Area ID (in ²)	14.360	14.360
Section Modulus (in ³)	5.708	4.475
Polar Section Modulus (in ³)	11.415	8.949
Torsional Strength (lbs/ft)	57,600	45,200
Tensile Strength (lbs)	554,000	436,000
Burst Pressure (psi)	13,300	12,200
Collapse Pressure (psi)	13,000	8,760

DRILL PIPE CONNECTION

OD (in)	6.500
ID (in)	3.500
Pin Tong Length (in)	9.00
Box Tong Length (in)	12.00
Connection	NC50 EIS™-L
Torsional Strength (lbs/ft)	57,500
Tensile Yield Strength (lbs)	1,020,000
Minimum Make-up Torque (lbs/ft)	27,100
Maximum Make-up Torque (lbs/ft)	35,500
Tool Joint/Pipe Body Torsional Ratio (New)	1.00
Thread Compound Friction Factor	1.0

DRILL PIPE ASSEMBLY

Approx Average Length (ft)	31.50
Open End Displacement (gal/ft)	0.36
Closed End Displacement (gal/ft)	1.02
Fluid Capacity (gal/ft)	0.71
Drift Size (in)	3.375
Adjusted Weight (lbs/ft)	23.34
Internal Plastic Coating	TK34P
Hardbanding	DURABAND NC

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.