

6-3/4" OD X 3.250" ID DRILL COLLAR, NON MAG SLICK, P530, NC50

DRILL COLLAR BODY

Nominal OD (in)	6-3/4
Nominal ID (in)	3.250
Pipe Wall Thickness (in)	1.750
Surface Finish	NON MAG SLICK
Grade	P530
Cross Sectional Area of Pipe Body (in ²)	27.489
Cross Sectional Area OD (in ²)	35.785
Cross Sectional Area ID (in ²)	8.296
Section Modulus (in ³)	28.571
Polar Section Modulus (in ³)	57.142
Momet of Inertia Drill Collar Body (in ⁴)	96.43
Polar Moment of Inertia Drill Collar Body (in ⁴)	192.85

DRILL COLLAR CONNECTION

Connection	NC50
OD (in)	6.750
ID (in)	3.250

DRILL COLLAR ASSEMBLY

Approx Average Length (ft)	31.00
Open End Displacement (gal/ft)	1.43
Closed End Displacement (gal/ft)	1.86
Fluid Capacity (gal/ft)	0.43
Drift Size (in)	3.125

All information contained herein is provided for reference/illustration purpose only. Data compiled are using information available from respective Manufacturer and/or other public sources. Even though due care has been exercised while compiling the data. PETRO PIPE accept no responsibility or liability for its accuracy, errors, omissions or misinterpretation. User is advised to examine the suitability and accuracy by their own resources.