

10KPRO

Portable Generator

Commercial / Residential

10,000 Watt Running

12,500 Watt Starting

Electric Start

680cc V-Twin



<5% THD SINE WAVE OUTPUT
AVR EQUIPPED
(Less Than 5% Total Harmonic Distortion)



Westinghouse

INNOVATION YOU CAN BE SURE OF

Specifications

Model Number:	10KPRO
Rated Wattage:	10,000
Surge Wattage:	12,500
Alternator:	<5% THD, All Copper
Voltage Regulation:	Automatic/Remote Mounted
Displacement:	680cc V-Twin
Type:	OHV, 4 Stroke
Rated RPM:	3600
Lubrication:	Pressure / Intercooled w/ Automotive Filter
Fuel Shut Off:	Manual / Electronic
Choke:	Manual
Starting:	Electric Only
Battery:	Included, 21 Ahr
Battery Charging:	120 Volt Charging Port / Engine Charging in Operation
Engine Protection:	Low Oil Shutdown
Emission Certifications:	EPA / CARB
Other Certifications:	CE
Receptacle Protection:	(1) 42 Amp Main Toggle (1) 30 Amp Toggle (2) 20 Amp Push Button / GFCI
Receptacles with Cover:	(2) NEMA 5-20R Duplex (1) NEMA L5-30R (1) NEMA L14-30R
Receptacles without Cover:	(1) CS6369 50 amp (1) 12 VDC Charge Port
User Interface:	VFT Meter / Self Scrolling (Volts / Frequency / Hour)
Fuel Capacity:	9.2 Gallons / 34.8 Liters
Fuel Type:	Unleaded <10% Ethanol
Fuel Gauge:	Built In Tank
Run Time 50% Load:	11 Hours
Oil Capacity:	1.9 Quart / 60.8 Ounces / 1.8 Liters (with oil filter change)
Oil Type:	10W-30 SAE
Handles:	(1) U Shaped Lift Bar - Included
Wheel Type:	(2) 3" Wide, Solid with Bearings
Bonus Accessories:	Oil, Funnel, Tool Kit, DC Battery Charger
Warranty:	1 Year Commercial / 3 Year Residential
Frame Diameter:	Steel HD 32 mm
Lifting Strap:	User Installed / Included
Grounding:	Bonded Neutral

Westpro Power Systems, LLC
W237 N2889 Woodgate Road, Unit B
Pewaukee, WI 53072 USA
www.westpropower.com

855-944-3571

Model: 10KPRO
January 2014

© 2014

WESTINGHOUSE, and INNOVATION YOU CAN BE SURE OF are trademarks of Westinghouse Electric Corporation. Used under license by Westpro Power Systems.

10KPRO Portable Generator

10000 RUNNING WATTS / 12500 STARTING WATTS

Westinghouse V-TWIN Engine



Heavy duty features including; 680cc, OHV engine with pressurized lubrication system, low oil shutdown, shock mounted oil cooler, automotive type oil filter and large 9.2 gallon fuel tank



Full Cage Steel Frame

Helps protect unit from damage, includes lifting kit

GFCI Protected Control Panel

Simple to use controls with covered outlets for tough working conditions



Data Center

Provides volts, frequency and hours for on-site use and proper maintenance cycles

Dimensions and Weights

Unit Length:	30.7 in / 780 mm
Unit Width:	31.1 in / 790 mm Assembled
Unit Height:	31.3 in / 795 mm
Unit Weight Dry:	300 lbs / 136 kg
Carton Length:	34.6 in / 880 mm
Carton Width:	27.5 in / 700 mm
Carton Height:	33.2 in / 845 mm
Carton Weight:	310 lbs / 141 kg
UPC:	855464003568



Westinghouse

INNOVATION YOU CAN BE SURE OF

