



3 100		
TECHNICAL SPECIFICATIONS	Power Source	Optional 110V, Self-Generating (with Emerge or Escalate®), 220V Option Available (with Transcend® or Escalate®)
	Cord Length	10' / 3.0M
	Drive System	Single Stage Drive System with Poly-V Belts
	Crank	3-Piece Forged Steel Crank System with Sealed Bearings
	Resistance Source	Hybrid Self-Generating Brake
	Resistance Levels	30
	Workload Range	20-450 Watts
	Frame Construction	Robotically Welded Heavy-Gauge Steel
	Pedals	Dual Sided and Weighted with Integrated Ratcheting Strap
	Seat	Ergonomic Seat with 15 Position Settings (Lever Under Seat)
	Handlebar Design	Multi-Position with Moisture Resistant Sleeves
	Contact Heart Rate Monitoring	Yes
	Wireless Heart Rate Monitoring	Polar® Compatible
AVAILABLE CONSOLES		Transcend ¹⁶ , Transcend ¹⁰ , Escalate ¹⁵ , Escalate ⁹ , Emerge
REGULATORY APPROVALS		ETL UL1647, CSA, CE, EN957, FCC, AS4092, C-TICK
EXTRAS	Accessories	Water Bottle Holder, Accessory Tray, Over Molded Reading Rack/Tablet Holder
PHYSICAL SPECIFICATIONS	Footprint	45" L x 24" W / 114 cm x 61 cm
	Machine Weight	146 lbs / 66 kg
	Shipping Weight	152 lbs / 69 kg
	Maximum User Weight	400 lbs / 181 kg
	Step-Over Height	16.75" / 42.5 cm
	Portability	2 Front Transport Wheels
WARRANTY	Warranty Type	Commercial (non-dues paying facilities with less than 8 hours of usage per day)
	Frame	Lifetime
	Parts	5 Years (Transcend ¹⁶ , Transcend ¹⁰ , Escalate ¹⁵ Consoles are 3 years)
	Labor	2 Years

Warranties outside the U.S. and Canada may vary - Please contact your dealer for details. Specifications subject to change without notice.















