



## SLOKY Preset Torque Screwdriver—LT Display Set



STS-TX-LT-S4

### Description

<b>Product:</b>	SLOKY Preset Torque Screwdriver—LT Display Set
<b>Models:</b>	STS-TX-LT-S4 for TORX
<b>Content:</b>	18 PCS in a Steel Stand 1) 6 PCS of LT Handle w/ Adapter, 1 PC of Each Size TX6, 7, 8, 9, 10, 15 2) 6 PCS of 1" Bit for TORX, 1 PC of Each Size, TX6, 7, 8, 9, 10, 15 3) 6 PCS of 2" Bit for TORX, 1 PC of Each Size, TX6, 7, 8, 9, 10, 15
<b>Packaging:</b>	Carton Box
<b>Dimension:</b>	7"X4"X3 3/4" (LWH)
<b>Weight:</b>	1.68 lbs

### Specifications

<b>Bits:</b>	High Alloy Steel, Hardness 58°-60°, Color Marked, 1/4" Hex Shank, 1" & 2" (L)
<b>Handle:</b>	Soft Grip LT Handle w/ Adapter, 2 3/4" X 3/4" X 2 5/8" (LWH)
<b>Adapters:</b>	Preset Torque, Color Marked, Magnetized, 1/4" Hex Shank, 1 1/2" (L), 1/2" (Dia.)

**Preset Torque:**

TX6	■	0.6 Nm/5.3 In-lb	TX7	■	0.9 Nm/8.0 In-lb
TX8	■	1.2 Nm/10.6 In-lb	TX9	■	1.4 Nm/12.4 In-lb
TX10	■	2.0 Nm/17.7 In-lb	TX15	■	3.0 Nm/26.6 In-lb

<b>Max. Actions:</b>	20,000 Times in Life-Time
<b>Allowance:</b>	±10%
<b>Patents:</b>	US8549963, US201202040734
<b>Applications:</b>	Cutting Tools/Machining, Parts Assembling/Electronics & Aerospace






















## SLOKY Preset Torque Screwdriver

### Features

<b>Replaceable:</b>	All three types of handle are replaceable. Any adapter fits any type of handle
<b>Color Marks:</b>	All the adapters and bits are color marked for easy pairing
<b>Accuracy:</b>	Patented adaptor ensures the preset torque is applied, with the tolerance of $\pm 10\%$
<b>Operation:</b>	Adapter will automatically release the connection with handle when the preset torque is reached and ends the screw tightening operation
<b>Signaling:</b>	Exceeding turns will only generate signal sound, no more torque is applied

### Configuration

 LT Handle	 0.6Nm/5.3 In-lb	 TX/IP 6	
	 0.9Nm/8.0 In-lb	 TX/IP 7	
	 1.2Nm/10.6 In-lb	 TX/IP 8	
	 1.4Nm/12.4 In-lb	 TX/IP 9	
	 2.0Nm/17.7 In-lb	 TX/IP 10	
	 3.0Nm/26.6 In-lb	 TX/IP 15	
	 5.0Nm/44.3 In-lb	 TX/IP 20	
	 5.5Nm/48.7 In-lb	 TX/IP 25	
	 HD Handle		
	 ST Handle		

### Notes

<b>Warning:</b>	Adapters are designed for manual operations, not suitable for use of power tools
<b>Compatibility:</b>	TORX Bits can be used on TORX-PLUS screws, but not vice versa
<b>Trade Mark:</b>	TORX & TORX-PLUS are the registered trademarks of Camcar Textron (USA)