

4184 E. Conant St. Long Beach, CA 90808 Tel. 888-900-1002 Fax. 310-900-1088 www.turboairinc.net

Project	•	
TIUJECI	•	

Item # :

Model # :

Qty :

Approval :

# **Condensing Unit**

### Model : TS045XR404A3





## \_\_\_\_ FEATURES / BENEFITS \_\_\_\_

- Blue anti-corrosion-fin increases the life span of the coil.
- Seamless inner groove copper tube increases the heat exchange rate by reducing the space between the fin and copper tube.
- Highest quality compressor in the world.



- Head pressure control stabilizes the freezing of liquid line, minimizes formation of flash gas to increase efficiency of the system, and prevents compressor damage by controlling high pressure.
- Experienced engineers have designed the system for maximum sfficiency.
- Fan Blades : Specifically matched with motors and coil for maximum air movement and cooling.

- Control box is designed for easy installation.
- Low pressure control is adjustable.
- All the parts are compliant with industry standards and interchangeale with readily available parts.
- Wiring : Easily accessible. Compressor comes with a wiring harness that is manufactured with connections that will not come loose with vibration.
- Control box and service valves are located outside for easy service.
- Base : Heavy duty steel. Legs are 2-1/6" tall
- Cabinet : Prepainted with galvanized body. Protects against corrosion.
- All products carry UL, cUL, ISO 9001 approvals.



# **Condensing Unit**

### Model : TS045XR404A3

#### PERFORMANCE CHART

	0°F(SST)	-10°F	-20°F	-25°F	-30°F	-35°F	-40°F
90'F(AMBIENT)	25950	21230	19020	16940	14990	13170	10070
95'F	24950	20410	18290	16290	14410	12670	9680
100'F	23950	19600	17560	15650	13830	12160	9290
110'F	21950	13960	14340	12680	11140	9830	8520

#### SPECIFICATION

Compressor	ZF13K4E-TF5			
Line Size	1/2" Liquid 1-1/8" Suction			
Receiver 90%	18			
Fan Data	1Fan (3760CFM)			
Dimensions	30.28(D) x 38.5W) x 27.28(H)			
Net Weight	285 Lbs			
Power Supply	208-230/3ph/60hz			
Compressor Amp	15			
MCA	21.4			
MOPD	35			


Design and specifications subject to change without notice

- Suction and discharge vibration eliminators with Discus compressors.
- Oil failure switch with Discus compressors.
- To prevent damage of compressor that resulted from liquid-compression, accumulator was installed in this units.

• To improve efficiency, installed oil separator


WARRANTY : 1 Year Compressor Warranty (4 Year extended warranty available)
1 Year Fan Motor and Parts Warranty

#### **PLAN VIEW**



(GERMAN

KNIFE)



**Toll Free** : 888-900-1002

(unit : inch)



I YEAR

