



Bloxygen

FINISH PRESERVER

Preserves oxygen or moisture-sensitive products:

- . oil-based paint
 - . varnish
 - . polyurethanes
 - . catalysts
 - . photo chemicals
 - . tung oil
 - . wood fillers
 - . urethanes
 - . stains
 - . gunpowder
 - . marine coatings
 - . printing chemicals
 - . sign paints
 - . fuel additives
 - . autobody chemicals
 - . coffee beans
 - . polyurethane glue
 - . epoxy resin
 - . wine and hops
 - . cooking oils
 - . seeds
- (Lacquer finishes and some latex paints will not benefit.)



For more information
visit us online at
www.bloxygen.com

Easy to Use (Spray, Seal & Store)

1. Twist the extension tube into tip.
2. Hold lid closely above container and spray towards side of container to avoid any splash.
3. Spray 2 full seconds for quarts and 4 full seconds for gallons.
4. Close lid immediately to seal in heavy gas.

Caution: Contents under pressure. Do not puncture or incinerate. Do not expose to heat or temperatures above 120°F (50°C). Misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Asphyxiant. Keep out of reach of children.

Contains: Argon. Non-flammable, inert and natural.

FULL CAN FEELS EMPTY

approx.
75
uses
in quarts*



Bloxygen[®]

FINISH PRESERVER

Inert Gas System prevents damage
from oxygen or moisture

**Eliminates
thickening
and
skin-over**



A product of IronWood Designs
P.O. Box 13838
San Luis Obispo, CA 93406
www.bloxygen.com



Environmentally Friendly Product
Please Recycle When Empty

Preserves stains, varnishes, oil-based paints,
chemicals, resins, and more

Net Contents 0.41 oz. (12g)

Full can feels empty