

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Fusion

TECHNICAL CHARACTERISTICS

Available Formats:	10x60, 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Zebrano	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Fabric	Number of Faces/Screens:	10x60:25, 12x24:40
Thickness in mm:	9mm	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	25%- dark colors	Surface Type:	Matte
Rectified:	Rectified	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.20%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)		Breaking Strength:	>35N/mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	ULA UHA		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	6
SqFt per Pallet:	465.20	Pounds per Carton:	49.3112
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".