

509 Water St. Bolivar, OH 44612 Phone: 330-455-1181 Fax: 330-455-1191

## US Technology Media Technical Data Sheet

## Magic II ® Type VIII

Magic II Type VIII is a composite blast media which has been treated with an anti-static agent, custom manufacted specifically for plastic media blasting. It is available in Mil-Spec, and Standard configurations.

Chemical Nature Inert

Appearance Granular

Color Multi-colored

Hardness Barcol 54-62

**MOHS 3.5** 

Elongation <1.0%

Compressive Strength 25000-45000 psi

Izod impact (1/8" specimen) 13-21 Jm<sup>-1</sup>

Explosibility – Minimum Explosive 0.079oz/ft<sup>3</sup>

Ignition Temperature 390°F

## Limits per MIL-P-85891A

Chlorine Content Trace

Ash Content 2.0% by wt Iron Content 0.10% by wt

Specific Gravity  $1.36 - 1.46 \text{ gm/cm}^3$ 

Extract Content 1% by wt

PH 4-8

 $\begin{array}{ccc} \text{Conductivity} & 100 \text{ mho/cm} \\ \text{H}_2\text{O Absorbtion} & 10\% \text{by wt} \\ \text{Heavy Particulate} & 0.02\% \text{ by wt} \\ \text{Light Particulate} & 1.0\% \text{ by wt} \\ \end{array}$