



Spectrol™

Technical Data Sheets

www.spectrolusa.com

05/22/2017

PRODUCT

Spectrol Universal Tractor Hydraulic Fluid J20D

FEATURES/BENEFITS

- Formulated for use in transmissions, hydraulic systems and final drive of modern farm and industrial wheel and crawler tractors.

APPLICATIONS

Spectrol Universal THF Fluids are acceptable for use in systems that require oils meeting John Deere J20D, Caterpillar TO-2, MTO, Oliver Type 55, Case Corporation JIC-143, 145, MS 1206, 1207, 1209, 1210 (TCH), Massey-Ferguson M1135, 1141, 1143, White Farm Equipment Q-1826, Allison C-4, Kubota UDT, Ford New Holland ESN-M2C134D (NH-410B), FNHA-2-C-201 and International Harvester B6, Volvo WB 101 specified oils.

TYPICAL PHYSICAL PROPERTIES

Density @ 15.6°C
Viscosity, @ 40°C
Viscosity, @ 100°C
Viscosity Index
Pour Point, °C
Brookfield @, -35 °C

Typical Results

7.319lbs/gal
60 cSt
9.5 cSt
130
-40
35000

ADDITIONAL INFORMATION

Please use proper handling and care that you would use with any motor oil.