


# ROTAVATOR® HR 15

For tractors from 25 to 60 HP





<sup>1</sup> Ideal for use in landscaping, nurseries, orchards, vineyards and on farms.

Water State of the

The HR-15 Rotavator has 7 different working widths ranging from 45 inches to 75 inches.

The side-drive is gear driven for extra strength.

# **ROTAVATOR MODEL HR 15**

#### **TECHNICAL SPECIFICATIONS**

MODEL	Working width cms- (ins)	Overall width cms - (ins)	Number of blades	Weight Kg (pounds)	Maximum offset positions (ins)
HR 15-45	115 - (45)	136 - (54)	27	245 (540)	21.5 — 23.5 17.5 — 27.5
HR 15-50	130 - (51)	154 - (61)	30	260 (573)	26.5 — 24.5 157.5 — 28.5
HR 15-55	140 - (55)	160 - (63)	33	275 (606)	26.5 22.5 — 28.5 32.5
HR 15-60	155 - (61)	179 - (70)	36	290 (639)	31.5 ————————————————————————————————————
HR 15-65	165 - (65)	186 - (73)	39	305 (672)	31.5 — 33.5 27.5 — 37.5
HR 15-70	180 - (71)	204 - (80)	42	320 (705)	31.5 27.5 39.5 43.5
HR 15-75	190 - (75)	212 - (83)	45	335 (739)	38.0 - 37.0 34.0 41.0

### **Standard equipment:**

**Power Range:** 25-60 HP with 540 rpm PTO. **Linkage:** Cat. 1 and 2, 3 point linkage.

**Tillage depth:** Adjustable by depth control skids. **Rotor speed:** Single speed rotor 225 rpm at 540 PTO.

Side drive: By gears train in oil bath.

Universal Joint Assembly: Bypy 106056N-61-007-243

**Clutch:** Bypy FF 1 type 6. **Parking stand:** As standard

Blades: As standard Howard P, universal L type (part n.º 9900/01).


## **Optional equipment:**

Front depth control wheels.

Howard speed P blade (part n.º 9953/54).



Rotor with 6 blades per flange. The standard version with universal blades.



Three positions of the mounting plates to fit any tractor. They are adjustable on a square tube to obtain offsetable positions.

HOWARD ROTAVATOR

the GUN MACHINERY specifications without prior notice. 14213 WASHINGTON ST.

Dealer:

IL.HWY 120 WEST WOODSTOCK, IL 60098 (815)- 338-0600



Thrige Agro AS P.O.Box 110 693 Dane Street Woodstock Illinois 60098