

# MATERIAL SAFETY DATA SHEET

## ACE PAINT THINNER

Page: 1

HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZ.	0
PPE	G



Printed: 03/24/2009

Revision: 10/03/2005

Date Created: 10/03/2005

### 1. Product and Company Identification

**Product Code:** ACE1677  
**Product Name:** ACE PAINT THINNER  
**Reference #:** ACE1677  
**Manufacturer Information**  
**Company Name:** W. M. Barr  
2105 Channel Avenue  
Memphis, TN 38113  
**Phone Number:** (901)775-0100  
**Emergency Contact:** 3E 24 Hour Emergency Contact (800)451-8346  
**Information:** W.M. Barr Customer Service (800)398-3892  
**Web site address:** www.wmbarr.com

### 2. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration	OSHA TWA	ACGIH TWA	Other Limits
1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	8052-41-3	95.0 -100.0 %	500 ppm	100 ppm	No data.
2. 1,2,4-Trimethylbenzene {Pseudocumene}	95-63-6	1.0 -2.0 %	200 ppm	50 ppm	No data.
3. Raffinates (petroleum), sorption process	64741-85-1	95.0 -100.0 %	1000 ppm	500 ppm	No data.
Hazardous Components (Chemical Name)	CAS #	OSHA STEL	OSHA CEIL	ACGIH STEL	ACGIH CEIL
1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	8052-41-3	No data.	No data.	250 ppm	No data.
2. 1,2,4-Trimethylbenzene {Pseudocumene}	95-63-6	500 ppm/(10min)	300 ppm	No data.	No data.
3. Raffinates (petroleum), sorption process	64741-85-1	No data.	No data.	750 ppm	No data.

### 3. Hazards Identification

#### Emergency Overview

Caution! Combustible. Keep away from heat, sparks, flame and all other sources of ignition. Vapors may cause fire. Vapors may travel long distances to other areas and rooms away from work site. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and all other sources of ignition anywhere in the structure, dwelling or building during use and until all vapors are gone from work site and all areas away from work site. Keep away from electrical outlets and switches. Beware of static electricity that may be generated by synthetic clothing and other sources.

#### OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

#### Health Hazards (Acute and Chronic)

Inhalation Acute Exposure Effects:

May cause dizziness; headache; watering of eyes; eye irritation; weakness; nausea; muscle twitches, and depression of central nervous system. Severe overexposure may cause convulsions; unconsciousness; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the

eye. Vapors may irritate eyes.

**Ingestion Acute Exposure Effects:**

Harmful or fatal if swallowed. May cause nausea; weakness; muscle twitches; gastrointestinal irritation; and diarrhea. Severe overexposure may cause convulsions; unconsciousness; and death.

**Chronic Exposure Effects:**

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. May cause jaundice; bone marrow damage; liver damage; anemia; and skin irritation.

**Signs and Symptoms Of Exposure**

Inhalation, ingestion, and dermal are possible routes of exposure.

**Medical Conditions Generally Aggravated By Exposure**

Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

**4. First Aid Measures**

**Emergency and First Aid Procedures**

**Inhalation:**

If user experiences breathing difficulty, move to air free of vapors, Administer oxygen or artificial medical assistance can be rendered.

**Skin Contact:**

Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

**Eye Contact:**

Flush with large quantities of water for at least 15 minutes and seek immediate medical attention.

**Ingestion:**

Do not induce vomiting. Call your local poison control center, hospital emergency room or physician immediately for instructions to induce vomiting.

**Note to Physician**

Call your local poison control center for further information.

**5. Fire Fighting Measures**

**Flammability Classification:**

Class II

**Flash Pt:**

105.00 F Method Used: Unknown

**Explosive Limits:**

LEL: 1.00 UEL: No data.

**Special Fire Fighting Procedures**

Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.

**Unusual Fire and Explosion Hazards**

No data available.

**Extinguishing Media**

Use carbon dioxide, dry powder, or foam.

**Unsuitable Extinguishing Media**

No data available.

## 6. Accidental Release Measures

### Steps To Be Taken In Case Material Is Released Or Spilled

Clean up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area.

Small spills:

Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

Waste Disposal:

Dispose in accordance with applicable local, state and federal regulations.

## 7. Handling and Storage

### Precautions To Be Taken in Handling

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

### Precautions To Be Taken in Storing

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

## 8. Exposure Controls/Personal Protection

### Respiratory Equipment (Specify Type)

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

### Eye Protection

Safety glasses, goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

### Protective Gloves

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

### Other Protective Clothing

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

### Ventilation

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

## 9. Physical and Chemical Properties

**Physical States:** [ ] Gas [ X ] Liquid [ ] Solid  
**Melting Point:** No data.  
**Boiling Point:** > 310.00 F  
**Autoignition Pt:** No data.  
**Flash Pt:** 105.00 F Method Used: Unknown  
**Explosive Limits:** LEL: 1.00 UEL: No data.  
**Specific Gravity:** No data.  
**Bulk density:** 6.659 LB/GA  
**Vapor Pressure:** No data.  
**Vapor Density:** No data.  
**Evaporation Rate:** No data.  
**Solubility in Water:** No data.  
**Percent Volatile:** 100.0 % by weight.  
**VOC / Volume:** 800.0000 G/L  
**Heat Value:** No data.  
**Particle Size:** No data.  
**Corrosion Rate:** No data.  
**pH:** No data.

**Appearance and Odor**

Water White / Free and Clear

## 10. Stability and Reactivity

**Stability:** Unstable [ ] Stable [ X ]

**Conditions To Avoid - Instability**

No data available.

**Incompatibility - Materials To Avoid**

Incompatible with strong oxidizing agents.

**Hazardous Decomposition Or Byproducts**

Decomposition may produce carbon monoxide and carbon dioxide.

**Hazardous Polymerization:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Polymerization**

No data available.

## 11. Toxicological Information

No data available.

**Carcinogenicity/Other Information**

No data available.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	8052-41-3	n.a.	n.a.	n.a.	n.a.
2. 1,2,4-Trimethylbenzene {Pseudocumene}	95-63-6	n.a.	n.a.	n.a.	n.a.
3. Raffinates (petroleum), sorption process	64741-85-1	n.a.	n.a.	n.a.	n.a.

**Carcinogenicity:** NTP? No IARC Monographs? No OSHA Regulated? No

## 12. Ecological Information

No data available.

## 13. Disposal Considerations

### Waste Disposal Method

Dispose in accordance with federal, state, and local regulations.

## 14. Transport Information

### LAND TRANSPORT (US DOT)

**DOT Proper Shipping Name** No data available.

## 15. Regulatory Information

### US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	8052-41-3	No	No	No	
2. 1,2,4-Trimethylbenzene {Pseudocumene}	95-63-6	No	No	Yes	
3. Raffinates (petroleum), sorption process	64741-85-1	No	No	No	

### US EPA CAA, CWA, TSCA

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Stoddard solvent {Mineral spirits; Aliphatic Petroleum Distillates; White spirits}	8052-41-3	No		Inventory	
2. 1,2,4-Trimethylbenzene {Pseudocumene}	95-63-6	No		Inventory, 4 Test	
3. Raffinates (petroleum), sorption process	64741-85-1	No		Inventory	

### SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

<b>Sec.302:</b>	EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.
<b>Sec.304:</b>	EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.
<b>Sec.313:</b>	EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.
<b>Sec.110:</b>	EPA SARA 110 Superfund Site Priority Contaminant List

### TSCA (Toxic Substances Control Act) Lists:

<b>Inventory:</b>	Chemical Listed in the TSCA Inventory.
<b>5A(2):</b>	Chemical Subject to Significant New Rules (SNURS)
<b>6A:</b>	Commercial Chemical Control Rules
<b>8A:</b>	Toxic Substances Subject To Information Rules on Production
<b>8A CAIR:</b>	Comprehensive Assessment Information Rules - (CAIR)
<b>8A PAIR:</b>	Preliminary Assessment Information Rules - (PAIR)
<b>8C:</b>	Records of Allegations of Significant Adverse Reactions
<b>8D:</b>	Health and Safety Data Reporting Rules
<b>8D TERM:</b>	Health and Safety Data Reporting Rule Terminations
<b>12(b):</b>	Notice of Export

### Other Important Lists:

<b>CWA NPDES:</b>	EPA Clean Water Act NPDES Permit Chemical
<b>CAA HAP:</b>	EPA Clean Air Act Hazardous Air Pollutant
<b>CAA ODC:</b>	EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)
<b>CA PROP 65:</b>	California Proposition 65

### International Regulatory Lists:

### EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

# MATERIAL SAFETY DATA SHEET

## ACE PAINT THINNER

Page: 6  
Printed: 03/24/2009  
Revision: 10/03/2005

- Yes  No Acute (immediate) Health Hazard
- Yes  No Chronic (delayed) Health Hazard
- Yes  No Fire Hazard
- Yes  No Sudden Release of Pressure Hazard
- Yes  No Reactive Hazard

### 16. Other Information

#### Company Policy or Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.