

# CONCRETECH

Nature Seal  
VOC 400 Concrete Sealer

## PRODUCT DESCRIPTION

Concretech Nature Seal is VOC compliant, quality, abrasion resistant, durable, solvent base acrylic sealers for concrete protection and highlighting color. Nature Seal uses the most advanced VOC exempt solvents to slow drying time and provide the most user friendly products.

## USES

For use on all interior and exterior concrete, stamped concrete, exposed aggregate, colored and flat work concrete. Nature Seal is ideal for architectural slabs, wood, walkways, driveways, ramps, bridge decks, columns and beams. It can also be used as a sealer on exposed aggregate and old or new concrete surfaces and as a finish coat for CSV12 and CSV15.

## PACKAGING

Nature Seal is ready to use and is available in 3.78 L /1 Gal., 18.9 L /5 Gal. and 207.9 L /55 Gal. containers.

## LIMITATIONS

Do not apply when temperature is below 7 C/45 F or above 28 C/82F. Precaution should be taken to condition materials in hot and windy conditions.

## INSTALLATION INSTRUCTIONS

Protect all surfaces that are not intended to receive sealer. Protect vegetation and landscaping. Clean all surfaces by scrubbing or pressure washing and rinse clean. Finish all touch up work, detailing, cleaning and surface coloration. Apply Concretech Nature Seal with pump up airless sprayer and back roll to establish continuous membrane. Surface must be touch-dry before applying second coat. Do not leave excess sealer in joints, grout lines or low spots. Contractors must use a sprayer designed for use with solvents. Other equipment may explode or fail, resulting in harm to persons or surrounding surfaces. Consult Material Safety Data Sheet (MSDS). All colored and imprinted concrete surfaces shall have a sealer or water repellent coating applied to protect the finish from moisture and oxidization. Apply Concretech Cure and Seal (CSV15) to freshly laid concrete as soon as possible. Apply Nature Seal 7 - 14 days later, depending on ambient cure conditions and mix design. Contact Concretech Technical Services for additional information.

## STORAGE

Store away from heat source, open flame or spark. Nature Seal is flammable. Store in cool dry area out of direct sunlight. Shelf life under normal conditions is two years. Store in sealed containers and ventilated areas only. Prevent contact with all sources of ignition, heat, spark and electric tools. Wear protective clothing, rubber gloves and eye protection. Prolonged exposure may result in respiratory illness, dizziness or damage to the nervous system. Contractor shall abide by all agency regulations for application, use, storage and disposal of solvent based materials. Keep away from children.

## PROPERTIES

Color : Clear  
Dry Time: 1-2 hours @ 21 C (70 F)  
Coverage: Apply at 225 – 275 square feet per gallon  
VOC Concentration: <400 grams per litre

## SAFETY PRECAUTIONS

First Aid: Flush contaminated areas immediately and seek medical attention. Remove contaminated clothing. Wash hands with soap and water. Flush eyes with clean water or eye wash solution.

## TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780.

Concretech Inc.'s sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street  
Surrey, BC V3S 3X1

[www.concretechproducts.com](http://www.concretechproducts.com)

Toll Free: 1.888.503.6780  
Fax: 1.604.357.1344  
Tel. 1.604.210.1147