

CONCRETECH

Grey/White Stamp

PRODUCT DESCRIPTION

Grey/White Stamp powder is a trowel grade topping designed for use as a stampable overlay, trowel overlay, patching and repair mortar. 28-day strength is 7000 psi. Grey/White Stamp powder is to be used with L-1 Polymer liquid for mixing and UltraBond Primer.

USES

For use as a topping from 1/4" to 1/2" thickness on all interior and exterior concrete, stamped concrete, colored and flat work concrete as well as any typical area where concrete or decorative color is used.

PACKAGING

Concretech Grey/White Stamp is available in 50 lb bags. Custom blended colors are available upon request. UltraBond Primer and Ultrabond Polymer L1 are available in 1 gallon and 5-gallon containers.

LIMITATIONS

Do not use over poor quality substrate. Do not place in thickness less than 1/4 or greater than 1/2 in one application. Do not use when temperature is less than 38° F, when temperature is expected to fall below 36° F or when inclement weather is expected during the first 24 hours after placement. Surfaces to be covered require at least two coats of UltraBond Primer as a primer before applying topping. Primer is to be touch dry between coats and dried clear before applying topping. Do not apply primer more than 24 hours before placement. Refer to Concretech Architectural Specifications for installation procedures, base preparation, forming and product information. Do not cure with plastic sheets, water or curing agents that may discolor the surface. Do not leave wood or other products on the surface while curing, as this will cause discoloration.

INSTALLATION INSTRUCTIONS

All concrete to receive the Grey/White Stamp shall be clean, free of oil, grease, dirt, efflorescence, drywall residue, excess moisture and foreign matter. Clean with commercial degreaser and rinse with plain water. Allow to fully dry before priming. Prime all surfaces with at least two coats of UltraBond Primer. Primer should be touch dry between coats and dried clear before applying topping. Pour 1 gallon of Ultrabond Polymer L1 liquid into clean pail and add 3/4 of the Grey/White Stamp powder and mix with drywall mud paddle on 1/2 drill for 30 seconds. Add remainder of Grey/White Stamp powder and mix for at least two minutes. Note: 10% more Ultrabond Polymer L1 may be added if

more workability is desired. For best results pour and trowel into place within 3 minutes of mixing. Remix material that is not placed within 5 minutes. Note: Slight color changes can be expected if addition ratios, batching procedures or mix times are altered. Pour mixed Grey/White Stamp onto surface in consistent thickness and trowel to smooth even finish. Hold trowel as flat as possible and lightly skim over surface using irregular motion to prevent repetitive trowel lines. Allow Grey/White Stamp to cure until plastic stage set is firm for stamping before using release powder or liquid release. See Technical Bulletin on each product before using. Allow Grey/White Stamp to cure until hard before removing release powder, cleaning, coloration and/or sealing. All colored concrete surfaces shall have a sealer or water repellent coating applied to protect the finish from moisture and oxidization. Apply Concretech Cure and Seal (CS 15) as soon as possible. Follow up with Concretech High Solids Sealer (CS 25 or CS 30) after 28 days. Follow Concretech technical bulletins for the applied product.

PROPERTIES

Base colors Grey or White
Custom colors available

SAFETY PRECAUTIONS

Caution – The product contains Portland cement and silica sand. Wear protective clothing, rubber gloves, and eye protection and dust respirator mask. Prolonged exposure may result in respiratory illness. Keep away from children.

First Aid -Flush contaminated areas immediately. Remove contaminated clothing. Wash hands with soap and water. Flush eyes with clean water or eye wash solution. In all cases seek immediate medical attention.

TECHNICAL SERVICES

Complete technical information is available from Concretech Inc. and its authorized applicators and distributors. In house laboratory testing is available for specialty applications. Technical services available in North America call toll free 1.888.503.6780

Concretech Inc.'s sole warranty is that our products have been manufactured to meet with our written specifications. The information herein is general information to assist our customers in determining whether our products are suitable for their applications. Our products are intended for sale to commercial and industrial customers. We require customers to inspect and test our products before use and to satisfy themselves as to contents, suitability and applications. Nothing herein shall constitute any other warranty, express or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent inferred. All patent and trademark rights are reserved. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

CONCRETECH

104, 2567 192 Street
Surrey, BC V3S 3X1

www.concretechproducts.com

Toll Free: 1.888.503.6780
Fax: 1.604.357.1344
Tel. 1.604.210.1147