

2006 MD3-Rider S-LSA







Call For Price

- TTAF & E: 321
- AVEO Red Barron Anti-Collision LED Strobe
- AVEO Flash LP 3-way Nav/ Position/ Strobe
- No Damage History
- All Logs
- Always Hangered
- Next Annual Due Nov. 2017

- Electric flaps & Electric Pitch Trim
- New Spare Main Tires & Tubes
- New Battery installed Oct. 2015
- Fire Extinguisher
- Two 12 volt outlets
- Skylight Windows
- Wheel Pans
- Window Vents

2006 MD3 RIDER S-LSA **Operational Specs**

Registration: N289AV

Serial Number: 026

TTAF: 321

Engine

TT: 321

- Rotax 912 S 100 HP @ 2380 rpm on propeller with anticorro exhauster w/ integral heating
- 5 Year hoses replacement Sept 2012
- Woodcomp SR 200 Propeller Three Blade (on the ground adjustable 1.68m with 35mm plug.)

Avionics:

- Garmin 396 Color GPS Built-in
- Garmin GTX 320-A Mode C Transponder
- Apollo SL40 760 Channel Digital Com Radio
- Grand Rapids EIS Model 4000
- Altimeter: VSI & ESI 4000
- Airspeed with probe Model 8000
- 6 place CD Stereo/ built-in intercom
- Tachometer plus EIS additional readout
- Hobbs hour meter
- ADI (electric) with GPS
- Directional Gyro (electric), Turn Coordinator
- Engine & Low Voltage alert light
- 406 mhz ELT AK-451-2D installed Sept/14
- Dual Stick mounted push to talk

Weight:

- Empty Weight: 700.9 lbs
- Max. Take-off Weight: 1267.2 lbs
- Useful Load: 566.3 lbs
- Payload with full fuel: 442.3 lbs

Performance:

- Max. speed: VNE 275 km/hr, 165 mph
- Max. cruising speed: VHmax 210 km/hod, 125 mph
- Cruise @ 4800 rpm (75%): 175 kph 110 mph
- Clean stall speed Vs1: 82km/hod, 50 mph
- Stall speed with flaps Vso: 62 km/hod, 38 mph
- Max. climb rate: 7 m/s, 1180 feet per minute
- Useful Fuel: 24.0 US gallons
- Fuel consumption @ 4800rpm: 13 L / Hour, 4.8 gph
- Range/Endurance: 500 miles/5.0 hours
- Maximum load factor: +4/-2

Dimensions:

Wing Span: 29'6" Cabin Width: 46" Length: 19'4"

Height: 7'7"

Wing Area: 106.56 Sq ft Forward Swept Wing: -3°