

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME **Terramare**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24*, 12x24*, 2x2 Mosaic 12x12 Sheet*, 3x24 Floor Bullnose* in Matte & Polished, *Chocolate Polished only.		
Style Description:		Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Contemporary Stone	Number of Faces/Screens:	
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer		Surface Type:	Matte & Polished with Nano Finish/Confirmed Sealed
Rectified:	Yes	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.09	Static COF:	Wet: 0.58 Dry: 0.73
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.59 (matte)
Scratch Hardness (MOHS)		Breaking Strength:	S=2005
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	ULA/UHA/UA		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.50	Pieces per Carton:	4
SqFt per Pallet:	496.00	Pounds per Carton:	70.53 lbs
Boxes per Pallet:	32	SqFt per Container:	12896.00
Pallets per Container:	26		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".