



SAATILENE HI-DRO

Saatilene HI-DRO is a high modulus, low elongation monofilament polyester screenprinting fabric with a proprietary surface treatment developed to meet the requirements of garment printing application. Especially designed to optimize the deposit when printing with water base inks, this new range was constructed maintaining the same mesh count and using thinner thread diameters.

KEY PRODUCTS CHARACTERISTICS

- Optimized mesh geometry and precise mesh openings due to the improved production process
- Excellent antistatic property
- Long lasting surface modification thanks to plasma treatment

YOUR BENEFITS

- Better printability
- Improved ink flow
- No degreasing pretreatment step prior to stencil processing, thanks to SAATI unique plasma surface treatment
- Excellent coverage on dark garments
- Less stencil cleaning work during printing
- Superior stencil adhesion, resulting in less stencil breakdown on press, delivering longer print runs far beyond other conventional treated fabrics
- Safe under exposure with all emulsion types, Photopolymer, Dual- Cure, Diazo and Capillary Films
- Excellent for use with abrasive printing conditions, inks and pastes.

ARTICLE				MESH COUNT		NOMINAL THREAD DIAMETER	MESH OPENING	OPEN AREA	FABRIC THICKNESS	THEORETICAL INK VOLUME	SPECIFIC CROSS- SECTION	MAXIMUM RECOMMENDED TENSION FROM-TO
				n°/cm		µm	µm	%	µm	cm³/m²	mm²/cm	N/cm
PE	AM	32.70	PW	32	81	70	245	61	110	67	0,123	30-35
PE	AM	43.64	PW	43	110	64	170	53	100	53	0,138	28-32
PE	AM	48.55	PW	48	112	55	153	55	90	50	0,185	24-26
PE	AM	55.48	PW	55	140	48	125	50	78	39	0,099	28-30
PE	AM	62.48	PW	62	157	48	109	46	77	35	0,112	28-30
PE	AM	78.40	PW	78	198	40	85	44	65	29	0,098	24-28
PE	AM	90.40	PW	90	229	40	68	38	62	24	0,113	20-24
PE	AM	120.31	PW	120	305	31	53	40	48	19	0,091	21-24