

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

MANHATTAN

TECHNICAL CHARACTERISTICS

Available Formats:	20x20, 13x13, 10x14 Glossy Wall, 2x2 Mosaic 13x13 Sheet, 3x13 Floor Bullnose, 2x10 Glossy Wall Bullnose		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	Multiple
Thickness in mm:	9.4mm - 9.8mm	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain (< .5%) Ceramic- Wall Tile Only
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: 0.50 Dry: 0.60
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.42
Scratch Hardness (MOHS)	6	Breaking Strength:	>250 lbf
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Resistant		

PACKING INFORMATION - 20x20 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.27	Pieces per Carton:	6
SqFt per Pallet:	780.96	Pounds per Carton:	67.5 lbs
Boxes per Pallet:	48	SqFt per Container:	N/A
Pallets per Container:	25		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".