

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME **PATINA**

TECHNICAL CHARACTERISTICS

Available Formats:	12x48, 8x32		
Style Description:	Wood	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Wood	Number of Faces/Screens:	28- 12x48, 45-8x32
Thickness in mm:	10.3 mm	Number of Punches/Molds:	2
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	No	Surface Type:	Matte, Textured
Rectified:	No	Recommended Grout Joint:	¾ mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	-0.5	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	300 lbs
Frost Resistant:	Yes	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Resist		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	3
SqFt per Pallet:	348.90	Pounds per Carton:	3
Boxes per Pallet:	30	SqFt per Container:	9769.20
Pallets per Container:	28		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".