



Specifications*

Energy Per Blow, Adjustable

Pump Setting 1	64 %	267.3 kNm	197,150 ft.lbs.
Pump Setting 2	75 %	313.2 kNm	231,020 ft.lbs.
Pump Setting 3	83 %	346.6 kNm	255,660 ft.lbs.
Pump Setting 4	100 %	417.6 kNm	308,025 ft.lbs.

Frequency 36 - 45 blows/min

Related Piston Stroke 3.2 - 1.6 m 10.5 - 5.3 ft.

Maximum batter w/o upper cyl. ext. 1:5 -

with upper cylinder extension 1:2 -

Fuel consumption at full load 36.0 L/hr. 9.5 gal./hr.

Oil consumption 3.6 L/hr. 0.95 gal./hr.

Approx. Weights

Hammer	24320 kg	53,616 lbs.
Piston	12500 kg	27,560 lbs.
Hammer with standard guiding	27330 kg	60,252 lbs.

Capacities

Fuel Tank	189 L	50 gal.
Oil Tank	60 L	15.8 gal.

Dimensions

A	- Length	7772 mm	25.5 ft.
LH	- Length, standard	8475 mm	27.8 ft.
B	- Center to trip	775 mm	30.5 in.
C	- Center to pump guard	572 mm	22.5 in.
D	- Width of hammer	1042 mm	41.0 in.
D1	- Width of trip	1206 mm	47.5 in.
W	- Minimum lead width	1067 mm	42.0 in.

*Technical data are subject to change without prior notice
 Operating energy based on piston stroke - values are approximate.
 Hydraulic start optional.