

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

|      |        |         |
|------|--------|---------|
| NAME | SERIES | SAMURAI |
|------|--------|---------|

| TECHNICAL CHARACTERISTICS                 |                        |                           |                   |
|-------------------------------------------|------------------------|---------------------------|-------------------|
| Available Formats:                        | 3X15 Ledger Field Tile |                           |                   |
| Style Description:                        |                        | Glaze Application Method: | HDIT Inkjet       |
| Visual Characteristics:                   |                        | Number of Faces/Screens:  | 54                |
| Thickness in mm:                          | 120                    | Number of Punches/Molds:  | 2                 |
| Modular Suitability:                      |                        | Body Type:                | Porcelain (< .5%) |
| Application:                              | Residential/Commercial | Color Body Unglazed:      |                   |
| Recycled Content:<br>Post or Pre Customer |                        | Surface Type:             | Matte             |
| Rectified:                                | No                     | Recommended Grout Joint:  | 2MM               |

| PRODUCT TESTING INFORMATION                                                                                             |     |                                             |     |
|-------------------------------------------------------------------------------------------------------------------------|-----|---------------------------------------------|-----|
| <i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i> |     |                                             |     |
| Water Absorption:                                                                                                       | 0.2 | Static COF:                                 |     |
| Shade Variation (1, 2, 3, 4)                                                                                            | V3  | Dynamic COF:                                | N/A |
| Scratch Hardness (MOHS)                                                                                                 | 8   | Breaking Strength:                          |     |
| Frost Resistant:                                                                                                        | Yes | Thermal Shock Resistance:                   | Yes |
| PEI/Abrasion Resistance:                                                                                                | IV+ | Deep Abrasion Test<br><175mm <sup>2</sup> : |     |
| Chemical Resistance:                                                                                                    |     |                                             |     |

| PACKING INFORMATION <i>Please inquire with Customer Service for additional sizes</i> |     |                     |    |
|--------------------------------------------------------------------------------------|-----|---------------------|----|
| SqFt per Carton:                                                                     |     | Pieces per Carton:  | 26 |
| SqFt per Pallet:                                                                     |     | Pounds per Carton:  |    |
| Boxes per Pallet:                                                                    | 70  | SqFt per Container: |    |
| Pallets per Container:                                                               | N/A |                     |    |

**Note:**

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".