

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

CANYON

## TECHNICAL CHARACTERISTICS

Available Formats:	18x18, 12x24, 13x13, 2x2 Mosaic 13x13 Sheet, 3x13 Bullnose		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	N/A
Thickness in mm:	9.6	Number of Punches/Molds:	N/A
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet: 0.81 Dry: 0.85
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	5	Breaking Strength:	>1300N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	GHA/GLA		

## PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.62	Pieces per Carton:	6
SqFt per Pallet:	464.80	Pounds per SqFt:	4.855 lbs
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	25		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".