

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

HINOKI

TECHNICAL CHARACTERISTICS

Available Formats:	6x24		
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Rustic	Number of Faces/Screens:	
Thickness in mm:	9mm	Number of Punches/Molds:	2
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte Textured
Rectified:		Recommended Grout Joint:	Min 2 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	Wet: 0.60 Dry: 0.70
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)	7	Breaking Strength:	Avr. 400lb
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Yes		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.58	Pieces per Carton:	14.00
SqFt per Pallet:	543.20	Pounds per Carton:	58.00
Boxes per Pallet:	40.00	SqFt per Container:	13580.00
Pallets per Container:	25.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".