

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Denim

TECHNICAL CHARACTERISTICS

| | | | |
|---|--|---------------------------|------------------|
| Available Formats: | 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose | | |
| Style Description: | Fabric | Glaze Application Method: | H.D.I.T. Inkjet |
| Visual Characteristics: | | Number of Faces/Screens: | 4 |
| Thickness in mm: | 9.5 | Number of Punches/Molds: | 12 |
| Modular Suitability: | No | Body Type: | Porcelain |
| Application: | Residential/Commercial | Color Body Unglazed: | Yes |
| Recycled Content: Post or Pre Customer | | Surface Type: | Matte / Textured |
| Rectified: | No | Recommended Grout Joint: | 2mm |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|------------|---|-------------|
| Water Absorption: | 0.05% | Static COF: | |
| Shade Variation (1, 2, 3, 4) | V3 | Dynamic COF: | 0.53 |
| Scratch Hardness (MOHS) | 7 | Breaking Strength: | 55.2 N / MM |
| Frost Resistant: | Yes | Thermal Shock Resistance: | Pass |
| PEI/Abrasion Resistance: | V | Deep Abrasion Test <175mm ² : | Yes |
| Chemical Resistance: | GA GLA GHA | | |

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

| | | | |
|------------------------|--------|---------------------|----------|
| SqFt per Carton: | 11.95 | Pieces per Carton: | 6 |
| SqFt per Pallet: | 573.60 | Pounds per Carton: | 47.44 |
| Boxes per Pallet: | 48 | SqFt per Container: | 11472.00 |
| Pallets per Container: | 20 | | |

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".