

EC6008A PARAFFIN CHEMICAL

Section: 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : EC6008A PARAFFIN CHEMICAL

Other means of identification : Not applicable.

PARAFFIN CHEMICAL Recommended use

Restrictions on use Refer to available product literature or ask your local Sales

Representative for restrictions on use and dose limits.

Company Nalco Champion Company

7705 Highway 90-A

Sugar Land, Texas 77478

USA

TEL: (281) 263-7000

Emergency telephone

number

(800) 424-9300 (24 Hours) **CHEMTREC**

Issuing date : 04/02/2015

Section: 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 2 Acute toxicity (Oral) : Category 4 Acute toxicity (Inhalation) : Category 4 Skin irritation : Category 2 Eye irritation : Category 2A Germ cell mutagenicity : Category 1B Carcinogenicity : Category 1B Reproductive toxicity : Category 2 Specific target organ toxicity -: Category 2

single exposure

Specific target organ toxicity -

single exposure

Specific target organ toxicity -

repeated exposure

: Category 2

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms





: Category 3 (Central Nervous System)



Signal Word : Danger

Hazard Statements : Highly flammable liquid and vapour.

Harmful if swallowed or if inhaled

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

EC6008A PARAFFIN CHEMICAL

May cause drowsiness or dizziness.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

: Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ eye protection/ face protection. Use personal protective equipment as required. Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Response:

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Rinse mouth. Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards : None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Concentration: (%)
Toluene	108-88-3	30 - 60
Light Aliphatic Naphtha	64742-89-8	30 - 60
Methanol	67-56-1	5 - 10
Oxyalkylate	Proprietary	1 - 5
Oxyalkylated alcohol	Proprietary	1 - 5
Xylene	1330-20-7	1 - 5
Cumene	98-82-8	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1

Section: 4. FIRST AID MEASURES

EC6008A PARAFFIN CHEMICAL

In case of eye contact Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention.

In case of skin contact : Wash off immediately with plenty of water for at least 15 minutes.

Use a mild soap if available. Get medical attention if irritation

develops and persists.

If swallowed : Do NOT induce vomiting. Never give anything by mouth to an

unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage. Get medical attention immediately.

If inhaled : Remove to fresh air. Treat symptomatically. Get medical attention.

Protection of first-aiders : In event of emergency assess the danger before taking action. Do

not put yourself at risk of injury. If in doubt, contact emergency responders. Use personal protective equipment as required.

Notes to physician : Treat symptomatically.

Most important symptoms and effects, both acute and

delayed

: See Section 11 for more detailed information on health effects and

symptoms.

Section: 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: None known.

Specific hazards during

firefighting

: Fire Hazard

Keep away from heat and sources of ignition. Flash back possible over considerable distance. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

: Decomposition products may include the following materials:

Carbon oxides

Special protective equipment : Use personal protective equipment.

for firefighters

Specific extinguishing

methods

: Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire

and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Ensure adequate ventilation. Remove all sources of ignition. Ensure clean-up is conducted by trained personnel only. Refer to protective

measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Methods and materials for : Eliminate all ignition sources if safe to do so. Stop leak if safe to do

EC6008A PARAFFIN CHEMICAL

containment and cleaning up

so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Flush away traces with water.

Section: 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes. Open drum carefully as content

may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Do not ingest. Keep away from fire, sparks and heated surfaces. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only with adequate ventilation.

Conditions for safe storage : Keep away from heat and sources of ignition. Keep in a cool, well-

ventilated place. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable

labeled containers.

Suitable material : The following compatibility data is suggested based on similar

product data and/or industry experience: Compatibility with Plastic Materials can vary; we therefore recommend that compatibility is

tested prior to use.

Unsuitable material : not determined

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Form of exposure	Permissible concentration	Basis
Toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		STEL	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA/Z2
		CEIL	300 ppm	OSHA/Z2
		Peak	500 ppm	OSHA/Z2
Light Aliphatic Naphtha	64742-89-8	TWA	500 ppm 2,000 mg/m3	OSHA Z1
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		STEL	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z1
Xylene	1330-20-7	TWA	100 ppm 435 mg/m3	OSHA Z1
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH

EC6008A PARAFFIN CHEMICAL

Cumene	98-82-8	TWA	50 ppm	ACGIH
		TWA	50 ppm	NIOSH REL
			245 mg/m3	
		TWA	50 ppm	OSHA Z1
			245 mg/m3	
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
			435 mg/m3	
		STEL	125 ppm	NIOSH REL
			545 mg/m3	
		TWA	100 ppm	OSHA Z1
			435 mg/m3	

Engineering measures : Effective exhaust ventilation system Maintain air concentrations

below occupational exposure standards.

Personal protective equipment

: Safety glasses with side-shields Eye protection

Hand protection Wear protective gloves.

Gloves should be discarded and replaced if there is any indication of

degradation or chemical breakthrough.

Skin protection : Wear suitable protective clothing.

Respiratory protection : When workers are facing concentrations above the exposure limit

they must use appropriate certified respirators.

: Handle in accordance with good industrial hygiene and safety Hygiene measures

> practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid

Colour colourless Odour : Alcoholic Flash point : 5.6 °C

Method: ASTM D 93, Pensky-Martens closed cup

pН : no data available Odour Threshold : no data available

Melting point/freezing point : FREEZING POINT: -30 °C, ASTM D-97

Initial boiling point and boiling : no data available

range

: no data available Evaporation rate Flammability (solid, gas) : no data available Upper explosion limit : no data available Lower explosion limit : no data available

Vapour pressure : 236 mm Hg (37.8 °C)

Relative vapour density : no data available

EC6008A PARAFFIN CHEMICAL

Relative density : 0.82 (-30 °C) Density : 6.81 lb/gal Water solubility : dispersible

Solubility in other solvents : no data available Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature

Thermal decomposition

: no data available : no data available

temperature

Viscosity, dynamic : no data available Viscosity, kinematic : 1.8 mm2/s (16 °C) Method: ASTM D 445

VOC : no data available

Section: 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Contact with strong oxidizers (e.g. chlorine, peroxides, chromates,

nitric acid, perchlorate, concentrated oxygen, permanganate) may

generate heat, fires, explosions and/or toxic vapors.

Hazardous decomposition

products

: Decomposition products may include the following materials:

Carbon oxides

Section: 11. TOXICOLOGICAL INFORMATION

exposure

Information on likely routes of : Inhalation, Eye contact, Skin contact

Potential Health Effects

Eyes : Causes serious eye irritation.

Skin : Causes skin irritation.

: May cause blindness if swallowed. Harmful if swallowed. May Ingestion

be fatal if swallowed and enters airways.

Inhalation : Harmful if inhaled. Inhalation may cause central nervous

system effects.

: May cause cancer. Suspected of damaging fertility or the Chronic Exposure

> unborn child. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure.

May cause genetic defects.

Experience with human exposure

EC6008A PARAFFIN CHEMICAL

Eye contact : Redness, Pain, Irritation

Skin contact : Redness, Irritation

Ingestion : Vomiting

Inhalation : Dizziness, Drowsiness

Toxicity

Product

Acute oral toxicity : Acute toxicity estimate : 771.59 mg/kg

Acute inhalation toxicity : Acute toxicity estimate : 15.28 mg/l

Exposure time: 4 h

Acute dermal toxicity : Acute toxicity estimate : 4,583 mg/kg

Skin corrosion/irritation : no data available

Serious eye damage/eye

irritation

: no data available

Respiratory or skin

sensitization

: no data available

Carcinogenicity

IARC Group 2B: Possibly carcinogenic to humans

Cumene 98-82-8 Ethylbenzene 100-41-4

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive effects : no data available

Germ cell mutagenicity : no data available

Teratogenicity : no data available

STOT - single exposure : no data available

STOT - repeated exposure : no data available

Aspiration toxicity : no data available

Section: 12. ECOLOGICAL INFORMATION

Ecotoxicity

EC6008A PARAFFIN CHEMICAL

Environmental Effects : Harmful to aquatic life.

Components

: Methanol Toxicity to fish

> LC50: 15,400 mg/l Exposure time: 96 h

> Oxyalkylate LC50: 1.5 mg/l Exposure time: 96 h

Components

Toxicity to daphnia and other : Methanol

aquatic invertebrates

EC50: > 10,000 mg/l Exposure time: 48 h

Ethylbenzene

EC50 Daphnia: 1.81 mg/l Exposure time: 48 h

Components

Toxicity to algae : Toluene

EC50 Chlamydomonas angulosa: 134 mg/l

Exposure time: 3 h

Methanol

EC50: 22,000 mg/l Exposure time: 72 h

Components

Toxicity to bacteria Toluene

EC50 Nitrosomonas Sp.: 84 mg/l

Exposure time: 24 h

Methanol > 1,000 mg/l

Components

Toxicity to fish (Chronic

toxicity)

: Toluene

NOEC: 1.39 mg/l Exposure time: 40 d Species: Coho Salmon

Methanol

NOEC: 7,900 mg/l Exposure time: 8.3 d

Components

Toxicity to daphnia and other : Toluene

aquatic invertebrates (Chronic toxicity)

NOEC: 0.74 mg/l Exposure time: 7 d

Species: Ceriodaphnia dubia

Persistence and degradability

no data available

EC6008A PARAFFIN CHEMICAL

Mobility

The environmental fate was estimated using a level III fugacity model embedded in the EPI (estimation program interface) Suite TM, provided by the US EPA. The model assumes a steady state condition between the total input and output. The level III model does not require equilibrium between the defined media. The information provided is intended to give the user a general estimate of the environmental fate of this product under the defined conditions of the models. If released into the environment this material is expected to distribute to the air, water and soil/sediment in the approximate respective percentages:

Air : 10 - 30% Water : 30 - 50% Soil : 10 - 30%

The portion in water is expected to float on the surface.

Bioaccumulative potential

no data available

Other information

no data available

Section: 13. DISPOSAL CONSIDERATIONS

The information presented only applies to the material as supplied. The classification or waste code may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Disposal methods : Hazardous wastes must be transported by a licensed

hazardous waste transporter and disposed of or treated in a properly licensed hazardous waste treatment, storage, disposal or recycling facility. Consult local, state, and federal

regulations for specific requirements.

The product should not be allowed to enter drains, water courses or the soil. Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in

an approved waste disposal facility.

Disposal considerations : Dispose of as unused product. Empty containers should be

taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (DOT)

The presence of an RQ component (Reportable Quantity for U.S. EPA and DOT) in this product causes it to be regulated with an additional description of RQ for road, or as a class 9 for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

EC6008A PARAFFIN CHEMICAL

Technical name(s) : TOLUENE UN/ID No. : UN 1993

Transport hazard class(es) : 3 Packing group : II

Reportable Quantity (per

package)

: 2,000 lbs

RQ Component : TOLUENE

Air transport (IATA)

The presence of an RQ component (Reportable Quantity for U.S. EPA and DOT) in this product causes it to be regulated with an additional description of RQ for road, or as a class 9 for road and air, ONLY when the net weight in the package exceeds the calculated RQ for the product.

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

Technical name(s) : TOLUENE UN/ID No. : UN 1993

Transport hazard class(es) : 3 Packing group : II

Reportable Quantity (per

package)

: 2,000 lbs

RQ Component : TOLUENE

Sea transport (IMDG/IMO)

Proper shipping name : FLAMMABLE LIQUID, N.O.S.

Technical name(s) : TOLUENE UN/ID No. : UN 1993

Transport hazard class(es) : 3
Packing group : II

Section: 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Toluene	108-88-3	1000	2000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements

of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established

by SARA Title III, Section 313:

 Toluene
 108-88-3
 30 - 60 %

 Methanol
 67-56-1
 5 - 10 %

 Xylene
 1330-20 1 - 5 %

1

Ethylbenzene 100-41-4 0.1 - 1 %

EC6008A PARAFFIN CHEMICAL

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

Cumene 98-82-8 Ethylbenzene 100-41-4

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene 108-88-3 Methanol 67-56-1

INTERNATIONAL CHEMICAL CONTROL LAWS:

TOXIC SUBSTANCES CONTROL ACT (TSCA)

The substances in this preparation are included on or exempted from the TSCA 8(b) Inventory (40 CFR 710)

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA)

The substances in this preparation are listed on the Domestic Substances List (DSL), are exempt, or have been reported in accordance with the New Substances Notification Regulations.

AUSTRALIA

All substances in this product comply with the National Industrial Chemicals Notification & Assessment Scheme (NICNAS).

EUROPE

The substances in this preparation have been reviewed for compliance with the EINECS or ELINCS inventories.

KOREA


All substances in this product comply with the Toxic Chemical Control Law (TCCL) and are listed on the Existing Chemicals List (ECL)

PHILIPPINES

All substances in this product comply with the Republic Act 6969 (RA 6969) and are listed on the Philippines Inventory of Chemicals & Chemical Substances (PICCS).

Section: 16. OTHER INFORMATION

NFPA:



Special hazard.

HMIS III:

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

Revision Date : 04/02/2015

Version Number : 1.0

EC6008A PARAFFIN CHEMICAL

Prepared By : Regulatory Affairs

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

For additional copies of an MSDS visit www.nalco.com and request access.