



PRODUCT DATA SHEETS

PENETRATING GEL LUBRICANT WITH TEFLON

DESCRIPTION

A high tack lubricating gel that provides superior lubrication from -30°F to +500°F. Penetrates as an oil to lubrication point then forms into a tacky, grease-like gel. Contains PTFE for added friction reduction. Provides superior stringing action. Resists water washout and weathering. Residual film prevents rust and corrosion. Safe on most plastics and paints.

FEATURES

- **HIGH TACK**
- **EFFECTIVE AT TEMPATURE RANGING FROM -30°F to +500°F**
- **PENETRATES AS AN OIL THEN SETUPS TO A TACKY GREASE LIKE CLEAR STRINGIN GEL**
- **RESISTS WATER WASHOUT**
- **PROVIDES AS A MOISTURE RESISTANT FILM**
- **PROTECTS AGAINST RUST AND CORROSION**

USE AND DIRECTIONS

For Use By: Machine Shops, Light and Heavy Manufacturing, HVAC + Plumbing and Other Trades, Automotive, and All Repair Operations

For Use On: Chains, gears, hinges, sprockets, cable, wire rope, slides, valves, bushings, pistons, shafts, rings

SHAKE WELL BEFORE USING. Remove cap and rotate actuator until orifice is pointed toward mark on valve cup. Spray holding can 12-14 inches away from surface to be treated. For hard to reach areas, insert extension tube into actuator orifice.

ATLANTIC SOLUTIONS, INC
125 N. CHATHAM PARKWAY CHAPEL HILL, NC 27517 Ph:800 476-0895
WWW.ATLANTICSOLUTIONSNC.COM