

Review of Machine Learning Algorithms for Predicting Power Requirements for Unmanned Marine Vehicles

Anirudh Singh Shaktawat¹, Sambandh Bhusan Dhal², Arun Agarwal³, Kabita Agarwal⁴

^{1,2}Department of Electrical and Computer Engineering, Texas A&M University, College Station, USA

³Department of ECE, ITER, Siksha O Anusandhan Deemed to be University, Bhubaneswar, Odisha, India-751030

⁴CV Raman College of Engineering, Department of Electronics and Telecommunication Engineering, Bhubaneswar, Odisha, India-752054

(Email: sambandh@tamu.edu, ug201311005@tamu.edu, arunagrawal@soa.ac.in, akkavita22@gmail.com)

Abstract- Unmanned Marine Vehicles (UMVs) are used for missions like carrying out surveys in water, search and rescue etc. These UMVs are operated on rechargeable batteries, so it is important to predict the battery/power requirements for these UMVs beforehand so that they can successfully complete their assigned missions without exhausting their batteries in the middle of the mission. When it comes to energy requirement prediction for unmanned vehicles, two paths can be followed. In the first approach, a model is built which incorporates all the measured quantities that quantify the degradation of the system (e.g. in our case, these quantities can be wind forces, lift and drag forces that result in power consumption), and implements mathematical equations to estimate the power requirements. This approach uses a physics based model which requires lot of mechanical parameters and may be quite noisy for prediction. Second is a machine learning approach in which the features are defined that can possibly affect the system, and then based on the past experiences of the system, the predictions are made in the future based on the features. In both cases, historical data is needed. This paper focuses on the second approach and reviews the literature to discover machine learning algorithms that can be helpful in predicting the energy requirements for unmanned marine vehicles in different missions.

Keywords- *UMV, machine learning, drag forces*

I. INTRODUCTION

In this paper, we have attempted to present an overview of how different machine learning algorithms and deep learning approaches have been used to predict the percentage of battery in rescue boats taking into consideration the different parameters that needs to be

considered in case of adverse weather situations. [2] has presented the features that can be used to build the machine learning models for predicting energy requirements for marine vehicles. It deals with the issue of predicting the ship's fuel requirement versus speed curve taking into consideration different weather conditions. It provides a good contribution to our research as it guides the feature selection for our research study.

There are not a lot of published works that directly focuses on predicting power requirements for unmanned marine vehicles but there are published works available from which the analogy can be taken to address our problem. For instance, [1] addresses the problem of predicting rate of oxygen consumption during maximal exercise and [3] deals with the issue of predicting power output generated from wind turbines. This paper attempts to classify these different independent studies which are analogous to our context and analyze the types of machine learning algorithms that these problems use for their prediction.

II. ANALYSIS OF ALGORITHMS

[1] deals with the problem of predicting maximal oxygen uptake (maximum rate of oxygen consumption) that would be required in different exercises. The most important features that it reports in its study are time, speed and grade (inclinations while running offering resistances to the subject). This study can be considered as an analogy to our problem of predicting rate of power consumption for UMV in different missions, as this also includes features like UMV speed and resistances from wind and water. Both of these problems can be classified into supervised learning category. Prior to [1], some studies have used Multiple Linear Regression (MLR) to solve these kinds of problems

and they also reported lower SEE (Standard Error of Estimate) values and high R (correlation coefficient), but they implemented the algorithm on a very small dataset (for instance, dataset of length 26). So, that is why the efficacy of the MLR algorithm in this context is skeptical since, in practice, MLR needs large amount of datasets to produce high R. [1] implements and compares four machine learning algorithms on its reasonable length dataset namely, Support Vector Machines (SVM), Generalized Regression Neural Networks (GRNN), Radial Basis Function Network (RBFN) and Decision Tree Forest (DTF). The paper implemented these algorithms on 15 different models each with a different set of feature selection. The results show that, although, in general, the performance of GRNN based prediction models is slightly better than the SVM, but for some models (feature set) SVM performed better. From the results, it can be concluded that depending upon the selection of feature set, both the Artificial Neural Networks (specifically, GRNN) and SVM algorithms work reasonably well for these kinds of problems.

Another analogy can be taken from the research studies dealing with day-ahead prediction of the output wind power from the wind turbine using machine learning techniques. Here, also many studies have applied different types of machine learning algorithms to predict the generated wind energy but the algorithms that have been proved successful for this type of problem are Artificial Neural Networks and Support Vector Machines. [5][6] reports a good performance in predicting the output wind power using SVM. SVM works by mapping the data into a feature space which is high-dimensional and then linear regression is used to calculate future values which is same as solving a problem which is not linear in the lower dimensional space of the original problem. [5][6] implement SVM using two kernel functions- traditional RBF and their newly proposed wavelet function. The results show that, in general, both have good performances for this problem with wavelet slightly better than RBF. In our context of UMV, the wavelet kernel function would take the input data i.e. wind speed, current speed, sine or cosine of wind and current directions etc. as a non stationary time series and decompose it into a stationary series in different frequency bands using wavelet decomposition, and then these predicted results of frequency bands would be combined to form the final result. This wavelet kernel function may prove very useful for our problem when we want to predict real time power requirements during the execution of the mission since in this case, our power requirement values are non stationary and continuously changing with time, whereas RBF function would be useful to estimate power/energy requirements for the mission before starting the mission.

However, [3] shows that SVM regression may deteriorate in terms of prediction accuracy when more input parameters are considered. The other technique is based on Artificial Neural Networks, which [9][10] have implemented in their studies. ANN models are based on the principle that the perceptions obtained through historical

data are reflected on future predictions using the logic of neural systems. Since the problem of power prediction for UMV has non linear structure which needs to obtain a correlation between the wind speed/direction, UMV speed/direction, Current speed/direction and the required power, ANN models are suitable for this kind of problem [4]. But [7] shows that ANN and SVM is directly correlated to the amount of training data. However as the size of the training data set increases, ANN models take more computational time to learn the data.

There are studies available which show that in order to achieve maximum possible prediction accuracy [8], we need a combination of different techniques. The most simple method of adding together is by simply averaging where all the predictors are assigned equal weights and final combination is an arithmetic mean of all the alternative predictions. The drawback of simple averaging is its high sensitiveness to extreme values. Regression is another such technique which is employed by [3]. It minimizes the combined Sum of Squared Errors (SSE) in order to assign appropriate weights to individual component predictions. [3] implements SVM, ANN (Conventional Feedforward Network), Simple Averaging and Regression, and compares them on Normalised Mean Squared Error (NMSE) metric as shown in table1. [4] implemented the mean combinations of ANN and SVM models (weighted) which yielded the minimum prediction error for their model.

ML Technique	Mean Absolute Error	NMSE(%)
SVM	43.59	3.17
ANN(CFNN)	34.53	1.65
Simple Averaging	32.97	1.58
Regression	28.31	1.03

Table1: Comparison of ML techniques [3].

The Results show that the highest accuracy was a result of regression technique used in the model and it outperformed all the other techniques clearly.

III. CONCLUSION

For the kind of a prediction problem that we want to solve, the two main algorithms or machine learning models that may prove highly effective are: Artificial Neural Networks and SVM. The critical point in using both these models is the selection of most optimal structure and parameters. If the parameters and structure we select is not proper, the bias/error of the model which we tend to calculate may result in abnormally unexpected higher values[4]. For a ANN model to have high accuracy, the number of neurons which we select is very important. If we have less number of neurons in the layers, an Artificial Neural Network cannot fit the data properly. On the other hand, if the number of neurons are too many in the hidden layers, then that overfits the model and would result in high bias of the

model. The model parameters which includes its weight/bias and the performance of the model are accessed by its Mean Square Error (MSE) which is a parameter accessed during training of the network.

For a problem in hand, SVM maps the data to a higher dimension to obtain accurate results. In our case, a linear regression model mapped to a high dimensional space is equivalent to a lower dimensional space without Support Vector Machines. The kernel function that we use in the model is selected after implementing all the possible kernel functions in the prediction models.

However, there exists limitations for both the models. The effectiveness of the SVM decreases as the size of the input parameter increases. Both of the algorithms need quite a large amount of data since their performance depends highly on the size of the training data set. But ANN gets computationally less efficient when the size of the training dataset increases. It takes more time to learn and predict which cannot be tolerated in case of predicting power requirements for UMV. For some input parameters, SVM may prove successful and for others ANN would do. So then, people in the past have applied combination techniques to get the best out of these two algorithms and improve the overall performance of the model, like Regression.

REFERENCES

- [1]. M. Fatih Akay, Ebru Cetin and Imdat Yarim, "Development of Novel Maximal Oxygen Uptake Prediction Models for Turkish College Students Using Machine Learning and Exercise Data", 9th International Conference on Computational Intelligence and Communication Networks (CICN), 2017, Girne, Cyprus, pp.186-189
- [2]. Nicolas Bialystocki, Dimitris Konovessis, On the estimation of ship's fuel consumption and speed curve: A statistical approach, Journal of Ocean Engineering and Science, Volume 1, 2016, Pages 157-166
- [3]. Solomon Netsanet, Jianhua Zhang, Dehua Zheng, Rahul Kumar Agarwal and Frankle Muchaharey, "An Aggregative Machine Learning Approach for Output Power Prediction of Wind Turbines", Texas Power and Energy Conference (TPEC), 2018 IEEE, College Station, TX, USA
- [4]. S. Buhan and I. Çadırcı, "Multistage Wind-Electric Power Forecast by Using a Combination of Advanced Statistical Methods," in IEEE Transactions on Industrial Informatics, vol. 11, no. 5, pp. 1231-1242, Oct. 2015. doi: 10.1109/TII.2015.2431642
- [5]. J. Zeng and W. Qiao, "Short-Term Wind Power Prediction Using a Wavelet Support Vector Machine," in IEEE Transactions on Sustainable Energy, vol. 3, no. 2, pp. 255-264, April 2012. doi: 10.1109/TSTE.2011.2180029
- [6]. Y. Liu, J. Shi, Y. Yang and W. J. Lee, "Short-Term Wind-Power Prediction Based on Wavelet Transform-Support Vector Machine and Statistic-Characteristics Analysis," in IEEE Transactions on Industry Applications, vol. 48, no. 4, pp. 1136-1141, July-Aug. 2012. doi: 10.1109/TIA.2012.2199449
- [7]. M. B. Ozkan and P. Karagoz, "A Novel Wind Power Forecast Model: Statistical Hybrid Wind Power Forecast Technique (SHWIP)," in IEEE

Transactions on Industrial Informatics, vol. 11, no. 2, pp. 375-387, April 2015. doi: 10.1109/TII.2015.2396011

- [8]. T. Clemen, Robert. (1989). Combining forecasts: A review and annotated bibliography. International Journal of Forecasting. 5. 559-583. 10.1016/0169-2070(89)90012-5.
- [9]. B. Bilal, M. Ndongo, K. H. Adjallah, A. Sava, C. M. F. Kebe, P. A. Ndiaye, V. Sambou (2018), "Wind turbine power output prediction model design based on artificial neural networks and climatic spatiotemporal data", in IEEE transactions on Industrial Technology (ICIT), doi: 10.1109/ICIT.2018.8352329
- [10]. Ali N. Celik, Mohan Kolhe, Generalized feed-forward based method for wind energy prediction, In Applied Energy, Volume 101, 2013, Pages 582-588, ISSN 0306-2619



Arun Agarwal has more than 14 years of professional, research, and teaching experience in wireless digital communication system. He is working as an Assistant Professor in ECE department at ITER (Faculty of Engineering and Technology), Siksha 'O' Anusandhan Deemed to be University, Bhubaneswar, Odisha, India. He completed B.E (2003) in Electronics & Telecommunication Engineering from Padmanava College of Engg., Rourkela and M.TECH (2010) in Telematics and Signal Processing from NIT, Rourkela, Odisha. Currently he is pursuing Ph.D from AMET University, Tamil Nadu, Chennai, India. His field of interest includes mobile wireless communication, MIMO-OFDM, LTE-A, 5G networks and signal processing. He has over 40 research articles published in journals, national and international conferences. He is member of IEEE & life member of ISTE, IETE, IACSIT, IEI professional society. He is also member of Editorial Board & Reviewer of many International Journals. He has also served as a TPC of many Springer and IEEE International Conferences.

(E-mail: arunagrawal@soa.ac.in).



Kabita Agarwal has more than 14 years of professional, research, and teaching experience in digital electronics and communication system. She is working as an Assistant Professor in ETC department at CV Raman College of Engineering, Bhubaneswar, Odisha, India. She completed B.E (2003) in Electronics & Telecommunication Engineering from Purushottam Institute of Engg. And Technology, Rourkela and M.TECH (2009) in Electronics & Telecommunication Engineering from BPUT, Rourkela, Odisha. Her field of interest includes digital electronics, basic electronics etc. She has over 10 research articles published in journals, national and international conferences. She is life member of IACSIT.
(E-mail: akkavita22@gmail.com).