

720P 8CH NVR Kit with 4pcs IP Camera



Model: NVR9F084C1MH

1. Features

- 4 * 720P IP Waterproof Indoor Outdoor Bullet camera, IR 20M
- 8 channel network video recorder, supports 8CH 720P/ 8CH 1080P IP Camera video input
- Support iPhone/iPad/Android Mobile monitoring
- Support ONVIF 2.2/ P2P Function(cloud service)/ Motion Detection/ Push Video
- Net cable 4pcs included(60ft each)
- Adaptor 4pcs included (for IP Camera)
- 1pcs 1TB HDD Preinstalled

2. Technical Specifications

IP Camera Specifications:	
Type	HD IR Waterproof Indoor Outdoor IP Bullet Camera
Image Sensor	1/4" 1.0Megapixel OV9712 CMOS
Resolution	1.0Megapixel 720P
Lens	3.6mm (3.6mm, 8mm Optional)
IR Light	30pcs 5Φ IR LEDS
Max. IR LEDS Length	20m
Frame Rate	PAL:1-25fps , NTSC:1-30fps
Compression	H.264 Main Profile Level 3.0
Bit Rate	0.1M ~ 6Mbps
Electronic shutter	1/25~1/100,000s
Low Lux	Color : 0.6Lux@F1.2 B/W : 0.08Lux@F1.2

Triple Stream	Support
Function	Reset, Password Protection
Cell phone monitor	iPhone, iPad, Android
3G network	N/A
POE	OPTIONAL
Power consumption	≤3W
Working temp	-10℃ ~ +55 ℃
Working humidity	10 ~ 85%
Dimension	L172mm*W74mm*H64mm
Type	8CH NVR
IP Camera Input	8CH 720P or 8CH 1080P IP Camera input
Audio Input	Through IP Camera Network Input
Protocol	ONVIF 2.2
CVBS	1ch, BNC
VGA	1ch, 1440×900,1280×1024,1024×768,800×600 Optional
HDMI	1ch, 1.3a, 1280×1024,1024×768,800×600 Optional
Resolution	720P, 1080P
Compression	H.264/MPEG 4 AVC, Main Profile 3.0
Frame Rate	1~30fps/D1,1~30fps/720P,1~30fps/1080P
Bit Stream Type	CBR / VBR
Video Bit Rate	D1 Max 2Mbps, 720P Max 4Mbps, 1080P Max 8Mbps
Audio Output	1ch,BNC (3.3Vp-p,4.7Kohms)
Audio Compress	G.711A, G.711U, G.726, AAC
Audio Bit Rate	16~128Kbps
Dual Stream	Support IP Camera Main Stream and Sub Stream
Playback	4CH 720P/960P or 2CH 1080P Sync playback
Motion Detection	Private protocol A1 or ONVIF Motion Detection
Hard Disk	1 SATA port, max support 4TB each
Network port	1 pcs, RJ45 10M/100Mbps self-adaptable Ethernet port
USB Interface	1 USB 2.0 ports
RS-485	Standard 485, half duplex,PTZ control
Dimension(W*D*H)	255x230x42(mm)
Weight	1.5Kg(without HDD)
Installation	Desk type
Power Supply	220V±10% 50Hz
Working Environment	-10 ~+55℃ / 10~90%RH / 86~106kpa