

# SERIES 985

# 20 mm

## Outdoor LED Message Center



985R-20D-16x112-RF shown in photo

Improve communication between you and your customers as they visit, or pass by your facility. Using the SCC Outdoor LED Message Center, your messages will be delivered with a style and clarity second to no other media. With an initial investment your advertising will continue day after day, and year after year with our highly reliable system.

### Uses include:

- Commercial Businesses
- Industrial Facilities
- Schools
- Churches
- Auto Dealerships
- Banks
- Shopping Centers
- Airports
- Restaurants
- Stadiums and Arenas
- Parking Facilities
- Casinos
- Auto Gas & Service Centers
- Billboard & Outdoor Advertising Companies
- Real Time Communication
- News, and Events
- Community Announcements
- Display Current Weather, Time, & Date
- Advertising and Promotions

# SERIES 985

# 20 mm

## Outdoor LED Message Center

### Features:

- Multiple font options along with custom downloadable images allow you to display virtually anything.
- SCC Sign Driver software to run your message center.
- Windows based communication software.
- Built in animation features can be used to attract your audience to the display.
- Display can stand alone or can be integrated with your existing signage.

### Power:

**Input:** 120/240 VAC 60/50 Hz, with Internal Circuit Breaker Sized Per Sign Layout.

### LED's:

**Single Color:** Super Bright Red, or Amber 5mm

**LED Rating:** Estimated 100,000 Hours

**Viewing Angle:** 100 Degree Horiz. Viewing Angle

**LED Pixel Pitch:** 0.78" - 20mm Center to Center (1 LEDs per pixel)

**Auto Dimming:** Signs equipped with Light Sensor to Adjust LED Brightness Based on Ambient Light Level (Option)

**LED Panels:** 16 Pixels in Height by 16 Pixels Width

**Panel Size:** 12.48" H by 12.48" W

### Enclosure:

**Material:** Light Weight Aluminum

**Construction:** NEMA 4, Single or Double Sided Enclosures.

**Finish:** Black Texture Paint Standard (other colors available).

**Mounting:** Pole, Wall, or Customized Ground Structure

### Labeling:

Customized Text, Logo, Company Name, Street Address, and Outlining.

### Communication:

**Input:** RS-485, RS-232, Ethernet, RF, Modem, and Many Others Available.

**Protocol:** SCC Multi-Use Protocol Using SCC Customized Software Package.

### General Specifications:

**Operating Temp:** -40 Degree F to 120 Degree F with internal Temp. Controlled Fans

**Lens:** Anti-Glare Lexan, or Exposed LEDs

### Part Number

Build Part Number Based on LED Tiles Used In Product.

Example: "985A-20D-32x112-RF" Enclosure size: 31"h x 94"w x 14"d

"Model Number" - "Pitch&Sides" - "# of Pixels High" x "# of Pixels Wide" - "Communication  
(R-Red, A-Amber) - (S-Single, D-Double) - Pixels High x Pixels Wide - (RF-Wireless, RS-485, Ethernet)  
985A - 20D - 32 x 112 - RF



Static Controls Corporation

Controls  
Diagnostics  
Communications

Telephone: (248) 926-4400 - Fax: (248) 926-4412  
30460 Wixom Road - Wixom, Michigan 48393  
[www.scccontrols.com](http://www.scccontrols.com)