# SAFETY DATA SHEET

#### 1. Identification

Company phone

**Product number** 1000033035

**Product identifier** 11 OZ UNIVERSAL RED SPRAY GREASE LB 12PK

Chem USA LLC **Company information** 

5400 NW 35th Avenue

Ft. Lauderdale, FL 33319 United States General Assistance 1-954-556-1700

1-866-836-8855 **Emergency telephone US** 1-952-852-4646

**Emergency telephone outside** 

US

01 Version #

Lubricant Recommended use None known. **Recommended restrictions** 

# 2. Hazard(s) identification

Flammable aerosols **Physical hazards** Category 1 **Health hazards** Serious eye damage/eye irritation Category 2A

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1

**OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes serious eye **Hazard statement** 

irritation. May cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear eye protection/face protection.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If inhaled: Response

Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical

advice/attention.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 3

long-term hazard

Hazard(s) not otherwise

classified (HNOC)

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

**Supplemental information** None.

Product name: 11 OZ UNIVERSAL RED SPRAY GREASE LB 12PK Product #: 1000033035 Version #: 01 Issue date: 12-06-2016

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
C12-C14 Isoalkanes		68551-19-9	20 - 40
Solvent Naphtha (Petroleum), Ligh Aliphatic	t	64742-89-8	20 - 40
Carbon Dioxide		124-38-9	2.5 - 10
n-Heptane		142-82-5	0.1 - 1
Octane		111-65-9	0.1 - 1
Other components below reportabl	e levels		10 - 20

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness.

Most important symptoms/effects, acute and

Ingestion

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Alcohol resistant foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

media Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters Fire fighting equipment/instructions

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move **Specific methods** containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

#### Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

## Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

#### Occupational exposure limits

Components	Type `	Value	
Acetone (CAS 67-64-1)	PEL	2400 mg/m3	
		1000 ppm	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
n-Heptane (CAS 142-82-5)	PEL	2000 mg/m3	
		500 ppm	
Octane (CAS 111-65-9)	PEL	2350 mg/m3	
		500 ppm	
<b>US. ACGIH Threshold Limit Values</b>			
Components	Туре	Value	
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
·	TWA	5000 ppm	
n-Heptane (CAS 142-82-5)	STEL	500 ppm	
	TWA	400 ppm	
Octane (CAS 111-65-9)	TWA	300 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
Acetone (CAS 67-64-1)	TWA	590 mg/m3	
		250 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	

#### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	
n-Heptane (CAS 142-82-5)	Ceiling	1800 mg/m3	
		440 ppm	
	TWA	350 mg/m3	
		85 ppm	
Octane (CAS 111-65-9)	Ceiling	1800 mg/m3	
		385 ppm	
	TWA	350 mg/m3	
		75 ppm	

#### **Biological limit values**

<b>ACGIH Biological</b>	<b>Exposure</b>	Indices
-------------------------	-----------------	---------

Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

# Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

**Other** Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**General hygiene** When using do not smoke. Always observe good personal hygiene measures, such as washing considerations after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

## **Appearance**

Gas. Physical state Aerosol. **Form** Color Not available. Not available. Odor **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point

1.4 °F (-17.0 °C) estimated

Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits

Flammability limit - lower (%)

0.9 % estimated

Flammability limit - upper

7 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 50 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.808 estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stabilityMaterial is stable under normal conditions.Possibility of hazardousHazardous polymerization does not occur.

reactions

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing,

redness, swelling, and blurred vision.

## Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results	
Acetone (CAS 67-64-1)			
<u>Acute</u>			
Dermal			
LD50	Guinea pig	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
	Rabbit	> 7426 mg/kg, 24 Hours	
		> 9.4 ml/kg, 24 Hours	
Inhalation			
LC50	Rat	55700 ppm, 3 Hours	
		132 mg/l, 3 Hours	
		50.1 mg/l	
Oral			
LD50	Rat	5800 mg/kg	

Components	Species	Test Results
		2.2 ml/kg
n-Heptane (CAS 142-82-5)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 29.29 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Octane (CAS 111-65-9)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rat	> 24.88 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
	n), Light Aliphatic (CAS 64742-89-8)	
<u>Acute</u>		
Dermal	D 11."	. 4000
LD50	Rabbit	> 1900 mg/kg, 24 Hours
Inhalation	D 4	. 5000
LC50	Rat	> 5000 mg/m3, 4 Hours
		> 4980 mg/m3
		> 4980 mg/m3, 4 Hours
		> 4.96 mg/l, 4 Hours
Oral		
LD50	Rat	4820 mg/kg

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Not applicable.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** 

Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-7	1)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
n-Heptane (CAS 142-	82-5)		
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

**Bioaccumulative potential** 

Partition coefficient n-octanol / water (log Kow)

 Acetone
 -0.24

 n-Heptane
 4.66

 Octane
 5.18

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

DOT

UN number UN1950

**UN proper shipping name** Aerosols, flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.1
Subsidiary risk Label(s) 2.1

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

#### **IATA**

**UN** number UN1950

Aerosols, flammable **UN proper shipping name** 

Transport hazard class(es)

**Class** 2.1 Subsidiary risk Label(s) 2.1

Not applicable. Packing group

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

**Packaging Exceptions** LTD QTY

**IMDG** 

UN1950 **UN** number **UN** proper shipping name **AEROSOLS** 

Transport hazard class(es)

Class 2.1 **Subsidiary risk** Label(s) 2.1

Not applicable. Packing group

**Environmental hazards** 

Marine pollutant No. F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Packaging Exceptions** LTD QTY Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

**DOT** 







Product name: 11 OZ UNIVERSAL RED SPRAY GREASE LB 12PK Product #: 1000033035 Version #: 01 Issue date: 12-06-2016

## 15. Regulatory information

**US federal regulations** 

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Acetone (CAS 67-64-1) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)** 

No

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

**DEA Exempt Chemical Mixtures Code Number** 

Acetone (CAS 67-64-1) 6532

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Acetone (CAS 67-64-1)

Solvent Naphtha (Petroleum), Light Aliphatic (CAS 64742-89-8)

**US. Massachusetts RTK - Substance List** 

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

n-Heptane (CAS 142-82-5)

Octane (CAS 111-65-9)

**US. New Jersey Worker and Community Right-to-Know Act** 

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

n-Heptane (CAS 142-82-5)

Octane (CAS 111-65-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)

Carbon Dioxide (CAS 124-38-9)

Product name: 11 OZ UNIVERSAL RED SPRAY GREASE LB 12PK
Product #: 1000033035 Version #: 01 Issue date: 12-06-2016

n-Heptane (CAS 142-82-5) Octane (CAS 111-65-9)

#### **US. Rhode Island RTK**

Acetone (CAS 67-64-1)

# **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2) Listed: February 27, 1987 Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997 Toluene (CAS 108-88-3) Listed: January 1, 1991 US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2) Listed: December 26, 1997

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico \*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

12-06-2016 Issue date

Version # 01

**Disclaimer** We cannot anticipate all conditions under which this information and its product, or the products of

other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written

based on the best knowledge and experience currently available.

**Revision information** Product and Company Identification: Alternate Trade Names Yes