

# **BPM FARM CLASS RULES**

Rubber tires only

2 WD only

No steel wheels or tire chains

7 mph max

- 1- 2WD Rubber tires only-No cut tires-Radials allowed
- 2- 5500 to 8500 lb classes are 18.4x38 tire size max
- 3- 9000 lbs and up are any tire size
- 4- Stock appearing blocks with stock appearing pump in stock location with sheet metal matching the rear end of that tractor
- 5-Hitch is 20" (5500-9500lb) and 22" (10500lb & up) high max and no shorter than 18" from center of rear axle. Hitch hole should be 3x3 1/4" Hitch to be stationary in all directions.
- 6- 11ft rule for front weights. (measured from center of rear axel)Rear weights to be mounted so the hitch is easily accessible.
- 7- Any tractor part falling off while hooked to the sled will result in DQ – all weights must be secure.
- 8- No down draft carburetors. Single bbl carburetors only.
- 9- Fuel limited to gas, LP, or diesel only. (Subject to random check) No extra injected fuels.(re: LP added to Diesel-No NOS etc.) Blue fuel-av gas etc - ok
- 10-Skid bars highly recommended for all tractors.
- 11-Any tractor running over 3000 rpm's must have a scatter blanket or a 3/8" steel shield covering the bell housing by 360 degrees. 4000 rpm max.
- 12-No excessive stripping – 3 pt arm removal okay. Judges decision is final.
- 13-No homemade front axels.
- 14-All tractors to be operated in a safe manner on and off the track.
- 15-Exhaust pipes to be straight- No curved pipes