

INDUSTRIAL DRYING OVEN (TRAY DRIER) RIC-32-TD

Double walled construction on heavy iron angle, inner chamber made of Mild steel painted with temp. resistant paint and outer finished with hammer tone paint, Insulation is done by glass wool. Temp. Range 50°C to 250°C controlled by Electronic Digital Temperature Indicator Cum Controller with an accuracy of $\pm 5^\circ\text{C}$, Air circulation is provided by heavy duty blower with ON/OFF switch indicator ventilators are provided on the top of Oven. Supplied with other accessories but without trays & trolley. Workable on Single Phase/ Three Phase 220 / 440 volts A.C. supply.

SPECIFICATIONS:



Inner Chamber	In feet	Cap of	Load	
	Size in mm		tray	
RIC-32TD-1	900 x 600 x 600	3 x 2 x 3	12	5KW
RIC-32TD-2	900 x 900 x 900	3 x 3 x 3	18	6KW
RIC-32TD-3	1200 x 900 x 900	4 x 3 x 3	24	7KW
RIC-32TD-4	1500 x 900 x 900	5 x 3 x 3	24	10KW
RIC-32TD-5	1800 x 900 x 600	6 x 3 x 2	36	10KW
RIC-32TD-6	1800 x 900 x 900	6 x 3 x 3	48	15KW
RIC-32TD-7	2400 x 900 x 900	8 x 3 x 3	60	15KW
RIC-32TD-8	2400 x 1200 x 1200	8 x 4 x 4	96	18KW

ADDITIONAL FACILITIES AT AN EXTRA COST: -

(a) Cost of Aluminum tray.

(b) Cost of Stainless Steel tray

(c) Electronic Timer 99.99 Hours.

RELIABLE INSTRUMENTS CO. (ISO 9001 CO.)

301, 2nd Floor, Mittal Commercial Complex, N.I.T-5, Faridabad, Haryana, India-121001

Tel.: 91-129-2410244, 4052611, 6450611; Telefax: 91-129-2410219;

M: 91-9818047375

Email: ricindfbd@gmail.com; ricind@rediffmail.com; ricind@yahoo.co.in;

Web: www.ricind.com

