

WILLSEAL VS. EMSEAL - CROSS REFERENCE GUIDE

WILLSEAL	Characteristics	EMSEAL	Characteristics
Willseal 150	Acrylic primary vertical seal in black or grey	25 V	Asphalt primary vertical seal in black
Willseal 250	Acrylic +/-50% horizontal join system – also available for split slab	20H (Asphalt) DSH (Asphalt) DSM (Acrylic)	DSM is only rated for +30%/-25% as dual seal
Willseal 600	Breathable, 600Pa primary or secondary applications	Backerseal/Greyflex	Secondary only, not UV or waterproof unless behind caulk
Willseal Seismic	DOW 790 color and Pecora 896 silicone colors, custom colors, and other sealants	Seismic Colorseal	DOW 790 and Pecora 896 silicone colors
Willseal Seismic DS	Coated on both sides: DOW 790 and Pecora 896 silicone colors, custom colors and other sealants	Double-sided Seismic Colorseal	Coated on both sides: DOW790 and Pecora 896 silicone colors
Willseal Seismic HS	Willseal Seismic supplied with epoxy for non-traffic horizontal use	Horizontal Colorseal	Seismic Colorseal supplied with adhesive for horizontal non-traffic use
Willseal FR-V	<ul style="list-style-type: none"> • Vertical 2 or 3 Hour Fire Rated • +/- 25% Movement (50% Total Movement) • +/- 50% Movement (100% Total Movement) • Available uncoated, coated on one side or coated on both sides. DOW 790 and Pecora 896 silicone colors, custom colors, other sealants, and pick resistant urethane (Dynaflex) 	WFR2 WFR3	<ul style="list-style-type: none"> • Vertical 2 or 3 Hour Fire Rated +/- 25% Movement (50% Total Movement) • Only Available with silicone and intumescent
Willseal FR-2H	<ul style="list-style-type: none"> • Horizontal 2 or 3 Hour Fire Rated • +/- 25% Movement (50% Total Movement) • +/- 50% Movement (100% Total Movement) • Available uncoated, coated on one side or coated on both sides. DOW 790 and Pecora 896 silicone colors, custom colors, other sealants, and pick resistant urethane (Dynaflex) 	DRF2 DFR3	<ul style="list-style-type: none"> • Horizontal 2 or 3 Hour Fire Rated +/- 25% Movement (50% Total Movement) • Only available with Silicone and Intumescent
Willseal Pureseal	Coated with NSF 61 approved coating for potable water applications	DSF	Coated with NSF 61 approved coating for potable water applications
Willseal Safeguard	Pick resistant urethane sealant (Dynaflex)	Security Seal	Pick resistant urethane sealant (Dynaflex)
Willseal Barrikade	Coating with highly chemically resistant (Vitone Coating System)	None Available	-
Willseal Spectraseal	Permeable colored secondary seal supplied in rolls	None Available	-
Willseal Coreseal	<ul style="list-style-type: none"> • EVA Closed Cell Foam • +/- 25% Movement (50% total Movement) • Vertical Applications 	None Available	-
Willseal Subseal	For use in below grade applications exposed or those exposed to head pressure	Submerseal	For use in submerged applications
Willseal Amorcrete	Winged gland & nosing	ThermaFlex	Winged gland & nosing
Willseal Acousti-Seal	Used as an air barrier and to reduce sound transmission, with or without silicone face(s)	QuietJoint	Sound Reduction