

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

SOHO

TECHNICAL CHARACTERISTICS

Available Formats:	4x16, 3x6, 3x6, 4x8 Wall Bullnose, 3x6 Wall Bullnose, 2x2 Dot-Mount 12x12 Mosaic		
Style Description:	Fume	Glaze Application Method:	Rotocolor
Visual Characteristics:	Subway Tile	Number of Faces/Screens:	N/A
Thickness in mm:	N/A	Number of Punches/Molds:	N/A
Modular Suitability:	Yes	Body Type:	Gres Porcelain (.1-.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Shiny/Gloss & Matte White
Rectified:	Yes	Recommended Grout Joint:	N/A

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	.1-.5%	Static COF:	Not rated
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	N/A
Frost Resistant:	No	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	Not Rated	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	N/A		

PACKING INFORMATION - 4x16 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11	Pieces per Carton:	25
SqFt per Pallet:	770	Pounds per Carton:	33.00 Lbs
Boxes per Pallet:	70	SqFt per Container:	N/A
Pallets per Container:	N/A		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".