

WEAR PADS

Wear Pad Part Number Breakdown

CWP V2 3 x 4

TYPE OF WEAR PAD

PWP, CWP, LWP, FWP
EG, LDWP, HDWP

PAD WIDTH

2", 3", 4", 5"
6", 8", 10", 12"

VELCRO OPTION

V1, V2

PAD LENGTH

Any length desired
for the application.

Polyester
Extra layer of protection
Model FWP

Felt
Good cut resistance.
Model FWP

Velcro
Allows for easy addition
and removal of wear pad,
1 or 2 inch
Model V1 & V2

Cordura®
Great protection from
abrasive surfaces
Model CWP

Dyneema®
Superior Strength using
the world's strongest fiber.
Best option for cut &
abrasion resistance. Light
Duty or Heavy Duty
Model LDWP or HDWP

Leather
Very rugged, good cut
resistance. Velcro not
available with leather.
Model LWP

Edge Guard
Helps protect the edges of
the sling
Model EG



WARNING

The top cause of synthetic sling failure is cutting. When a sling is cut, property damage and personal injury or death could result. Wear pads can help reduce this problem by supplying a buffer between the load edge and the sling. Be sure to inspect wear pads for damage. If the wear pad is damaged, the sling may also be damaged.