



SUBMITTAL DATA
SHEET METAL FITTINGS

**Flange & Gasket
STRAIGHT COLLARS**

Straight Fittings

(Tolerance on all sizes +/- 1/8")

Nom. Dia.	O.D.	Length No Damper Standard Damper	Length With Build Out	Flange O.D.
4"	3.875	5"	7"	6
6"	5.875	5"	7"	8
8"	7.875	5"	7"	10
10"	9.875	5"	7"	12
12"	11.875	5"	7"	14
14"	13.875	5"	7"	16
16"	15.875	5"	7"	18
18"	17.875	5"	7"	20
20"	19.875	5"	7"	22

Flange – 1" wide, galvanized steel

Gasket – 1/8" PE Foam, PSA

Fitting Model

- FLSOC No Damper
- FLSOCD Standard Damper – Spring End Bearing with Handle and Wingnut
- FLSOCD1 2" Damper Handle Extension
- FLSOCD3 2" Build Out – 3/8 " square shaft, Nylon End Bearings and Locking Handle

Standard Construction

- G90 Galvanized Steel, 26 Ga. thru 12" Dia., 24 Ga. on 14" Dia. and above

Gauge Options

- 24 Gauge
- 22 Gauge
- 20 Gauge
- Other _____

Material Options

- Galvanized Steel
- Aluminum
- Stainless Steel
- Other _____