

General Rules

All classes must have 5 or more entries to receive payout. If two vehicles hook in the same class, only the first hook will be eligible for payout. Judges decisions are final.

Tractor Class Rules

4 MPH Stock Tractor Rules

- 4 MPH Speed limit
- Tractor must have one engine
- Engine must have been available for make of tractor.
- No tires larger than 18.4" (excludes 8,500-lb stock), top cuts are allowed, no full cuts
- 20" hitch height
- Wheelie bars and kill switch are recommended

6 MPH Stock Tractor Rules

- 6 MPH Speed limit
- Tractor must have one engine
- Engine must have been available for make of tractor.
- No tires larger than 18.4", full cuts are allowed
- 20" hitch height
- Wheelie bars and kill switch are mandatory

Open Tractor Rules

- All open classes have no tire limit
- Rotating clutch assembly must be totally surrounded with a minimum of 3/16" steel, 1/4" aluminum, or use an SFI 4.1 or 4.2-approved blanket. Blanket must completely surround clutch. Two blankets will be legal to accomplish this.
- Tractor must have a steel flywheel, tie bars, wheelie bars, kill switch, cross bolts, and side shields.
- 20" hitch height, and 18" from center of rear axle
- Roll-caged tractor drivers must wear a helmet while pulling

Hot Farm Rules

- 20.8" maximum tire size
- 20" hitch height
- Tractor must have only one 2.8 or smaller turbo
- Tractor must use stock appearing frame
- Tractor must have one engine, a steel flywheel, tie bars, wheelie bars, kill switch, cross bolts, and side shields.
- Rotating clutch assembly must be totally surrounded with a minimum of 3/16" steel, 1/4" aluminum, or use an SFI 4.1 or 4.2-approved blanket. Blanket must completely surround clutch. Two blankets will be legal to accomplish this.
- Roll-caged tractor drivers must wear a helmet while pulling
- Front weight bracket must not exceed 13 feet from the center of the rear axle (excluding tow hook)

6,500-7,000 lb Unlimited Open Farm Rules

- 6,500 lbs max tire 24.5-32 *(20.8-38 accepted at 6,500 lbs)*
- 7,000 lbs max tire 18.4-38
- All one class
- Safety:
 - Cage or roll bar
 - Harness or seat belt
 - Wheelie bars
 - Tie bars
 - Steel flywheel - clutch set up
 - Safety blanket
 - Kill switch - air (guillotine) and fuel shut off (fuel dump of three way valve)
 - Side shields .060 thick
 - 360-degree shield around stock harmonic balancer (if you are running belts for the alternator or water pump then a ½ plate directly below the balancer from side to side of frame must be present)
 - ¾ cross bolts in exhaust pipe minimum grade 5
 - Turbo's out of hood must be covered with at least .060 sheet metal
 - Recommended but not mandatory ¾ cable around block and head
 - Helmet
- Must be a transmission and rear end of a farm tractor
- No component tractors
- 114" wheelbase - 13ft from center of back axel to the furthest point forward not including the tow hook
- Hitch must be at least 18" from center of back axel and be ridged in all directions
- Any agricultural V8 Diesel is acceptable (3208 cat or a Perkins)
- NO Automotive V8 engines

UOF Update

OK I am going to try and clear the air on the new addition to our rules. We added that the 20.8-38 could be run in the class but at 6500 lbs only, so the maximum tire size for the 6500 lbs is anything up to a 24.5-32, and the maximum tire size for 7000 lbs is 18.4-38s. No exceptions. And for new people interested in the class it is a combination weight class. Both 6500 and 7000lb tractors pull together.

And we are going to change the points for this year and it will go as follows: points will be given for show up and hook, if the pull is called because of weather or sled breakage you will receive show up points. If the pull proceeds after the delay, anyone leaving before the hook will forfeit their show up points. If you are interested in running for points this year, we are going to put \$50 per tractor in the kitty for the banquet and will have a sponsor decals and an ID number for your tractor that will have to be present at the class pulls in order to receive points. Rule question and to become eligible for points, call Rich at 330-418-0003.

Truck Class Rules

6,500 lb. Limited Street Gas Rules

- This class will follow all Buckeye Power Productions rules.

6,500 lb. Cheater Street Gas Rules

- This class will follow all Buckeye Power Productions rules.

6,500 lb. Open Gas Rules

- 26" hitch (no exceptions)
- DOT tires only
- Naturally aspirated, no nitrous, no propane, no water injection
- Hanging weights allowed, but must not exceed 60" from center of front axle
- Front and rear u-joint shields are required (no exceptions)
- Trucks must either have a blow proof bell housing or a SFI 4.1-4.2 scatter blanket surrounding the clutch (NO CAST IRON FLYWHEELS)
- Top five trucks will be inspected.

8,000 lb. Work Stock Diesel (Buckeye) Rules

- This class will follow all Buckeye Power Productions rules.

8,500 lb. 2.6 Smooth Bore Diesel Rules

- This class will follow all Buckeye Power Productions rules.

•

8,500 lb. 3.0 Smooth Bore Diesel Rules

- This class will follow all COTPC rules.

Street Stock Semi Rules

- Trucks must have valid license and registration
- Must be street legal
- Drivers must supply their own hitches.