

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

QUEENS STONE

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24, 12x24, 12x12, 9.5x11 Hexagon, 3x14, 2x2 Mosaic 12x12 Sheet, 3x12 Bullnose		
Style Description:	Waethered/Worn	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Cement Stone Mix	Number of Faces/Screens:	20 to 60, depends on size
Thickness in mm:	10mm; 10.5 on Hex	Number of Punches/Molds:	N/A
Modular Suitability:	Yes	Body Type:	Porcelain (<.5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	Pre-consumer 20%	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	< .5%	Static COF:	Wet: 0.60 Dry: 0.60
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	N/A
Scratch Hardness (MOHS)	8	Breaking Strength:	≥ 35N mm <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	N/A
Chemical Resistance:	N/A		

## PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.84	Pieces per Carton:	6
SqFt per Pallet:	473.60	Pounds per SqFt:	4.79 Lbs
Boxes per Pallet:	40	SqFt per Container:	N/A
Pallets per Container:	N/A		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".