

## **TECHNICAL SPECIFICATIONS**

PROJECT:		
PRODUCT NUMBER:	DATE:	
NOTES:		

## MiniPendant™ LED Drop Pendant



## **SPECIFICATIONS**

SPECIFICATIONS	made in ook		
Power Consumption	2.7 – 3.6 watts		
Lumens	170 lumens		
Luminous Efficacy	63 lm/w		
Voltage	12V DC		
Power Factor	0.90 (at 75-100% load)		
Color Temperature —	Warm White: 2700K		
- Color Temperature	Neutral White: 3500K		
Beam Angle	120°		
<b>Diode Nativity</b>	Nichia NS6		
Rated Life	35,000 hours minimum		
Warranty	5 year limited – luminaire 2 year limited – power supply		
Power Supply Ordered Separately	12V DC – Class 2 only Regulated, Constant Voltage		
Dimming & Control Ordered Separately	NuLEDs LumiDrive™ LD-003		
Certifications	Indoor only		
& Code Requirements	Made in USA		
Dimensions	$\varnothing$ 2", 7" Length		
Trims/Finish	Anodized Aluminum (standard)		
Mounting	Ceiling mount Comes with 6' lead cable (standard)		
Wiring	Parallel		
Applications	Restaurants Bars & Clubs Kitchens Accent Lighting		



The MiniPendant $^{\text{m}}$  is a sleek and unobtrusive LED drop pendant with a classy anodized aluminum finish.

Great over restaurant dining tables and bar lighting, the MiniPendant<sup>m</sup> is ideal for commercial & residential applications.



## **Ordering Information**

<u>PRODUCT</u>		COLOR TEMPERATURE		<u>FINISH</u>
MPN-LC11	-		-	AL

**27** = 2700K **AL** = Anodized Aluminum (standard) **35** = 3500K

Example Product #
MPN-LC11-35-AL
MiniPendant™ 3500K with
anodized aluminum finish