

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

NAME	SERIES	NUVO CALACATTA
------	--------	-----------------------

TECHNICAL CHARACTERISTICS			
Available Formats:	24X24, 12X24, 2x2 Mosaic 12x12 Sheet, 3X24		
Style Description:	Marble	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Calacatta	Number of Faces/Screens:	15
Thickness in mm:	10.85	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain (.5%)
Application:	Residential / Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Polished
Rectified:	Yes	Recommended Grout Joint:	No less than 1/8"

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<.5%	Static COF:	Wet: 0.58 Dry: 0.63
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.19
Scratch Hardness (MOHS)		Breaking Strength:	2370N (34N/mm ²)
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	Passes
Chemical Resistance:	Yes		

PACKING INFORMATION - <i>Please inquire with Customer Service for additional sizes</i>			
SqFt per Carton:	10.98	Pieces per Carton:	3
SqFt per Pallet:	395.28	Pounds per Carton:	4.91 lbs
Boxes per Pallet:	36	SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".