

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

**Imarmi**

## TECHNICAL CHARACTERISTICS

Available Formats:	20x20 Polished, 20x20 Matte, 5.5x33, 4x12, 3x20 Polished Bullnose & 3x20 Bullnose		
Style Description:	Marble Effect	Glaze Application Method:	Inkjet
Visual Characteristics:	Plain Tile	Number of Faces/Screens:	20x20 = 13
Thickness in mm:	10 mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	PORCELAIN (>.5%)
Application:	Residential / Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	0	Surface Type:	Matte & Glossy / Polished
Rectified:		Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	Wet: Dry:
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	0.34
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	YES	Thermal Shock Resistance:	Resist
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - 20x20 *Please inquire with Customer Service for additional sizes*

SqM per Carton:	1.63	Pieces per Carton:	6
SqM per Pallet:	39.12	Pounds per Carton:	47.20
Boxes per Pallet:	24	SqM per Container:	1290.96
Pallets per Container:	33		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".