

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

MYTHOS

TECHNICAL CHARACTERISTICS

| | | | |
|---|------------------------|---------------------------|------------------------|
| Available Formats: | 6x40 | Glaze Application Method: | HDIT Inkjet |
| Style Description: | Waxed Wood | Number of Faces/Screens: | 30 ,except Almond = 18 |
| Visual Characteristics: | Wood | Number of Punches/Molds: | N/A |
| Thickness in mm: | 10 mm | Body Type: | Porcelain (<.5%) |
| Modular Suitability: | No | Color Body Unglazed: | No |
| Application: | Residential/Commercial | Surface Type: | Matte |
| Recycled Content: Post or Pre Customer | 40% | Recommended Grout Joint: | Minimum 3/16" |
| Rectified: | No | | |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|------|--|---------------------|
| Water Absorption: | <.5% | Static COF: | Wet: 0.56 Dry: 0.76 |
| Shade Variation (1, 2, 3, 4) | V4 | Dynamic COF: | N/A |
| Scratch Hardness (MOHS) | 7 | Breaking Strength: | 450 |
| Frost Resistant: | Yes | Thermal Shock Resistance: | Yes |
| PEI/Abrasion Resistance: | IV | Deep Abrasion Test <175mm ² : | Yes |
| Chemical Resistance: | Yes | | |

PACKING INFORMATION

| | | | |
|------------------------|--------|---------------------|--------|
| SqFt per Carton: | 13.23 | Pieces per Carton: | 8 |
| SqFt per Pallet: | 555.66 | Pounds per Carton: | 59 Lbs |
| Boxes per Pallet: | 42 | SqFt per Container: | N/A |
| Pallets per Container: | N/A | | |

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".